Index of Syntax Rules

A

action-stmt, 19
action-terminated-loop-construct, 144
actual-arg
  (function reference), 170
  (subroutine reference), 169
actual-arg-list, 169, 170
actual-keyword-arg, 172
actual-keyword-arg-list, 172
align-directive, 518
allocatable-attr-spec, 56
allocatable-stmt, 60
allocate-object, 68, 69
allocate-stmt, 67
allocation, 67
alphanumeric-character, 7
alphanumeric-or-other-character, 9
alternate-return-spec, 169
arithmetic-if-stmt, 158
array-constructor, 81
array-constructor-value, 81
array-element-designator, 74
array-section, 76
array-spec, 32
assign-stmt, 156
assigned-goto-stmt, 157
assignment
  assignment-stmt, 118
  forall-assignment, 128
assumed-shape-array-spec, 35
assumed-shape-spec, 35
assumed-size-array-spec, 37
attr-spec, 39, 49
axis-descriptor, 511

B

b-op (binary operator), 84
backspace-stmt, 245
binary-constant, 25
blank-edit-desc, 282
block, 134
block-data-program-unit, 114
block-if-construct, 135
block-loop-construct, 140
  (DO TIMES), 142
  (DO WHILE), 143
  (DO), 141
boz-literal-constant, 25
byte-length, 41

C

call-stmt, 169
case-construct, 137
case-expr, 137
case-selector, 137
case-value, 138
case-value-range, 138
char-entity-decl, 45
char-expr, 92
char-length, 46
char-literal-constant, 29
char-literal-edit-desc, 283
char-operation, 92
char-primary, 92
char-variable, 93
character, 7
close-spec, 242
  (STATUS), 243
close-stmt, 242
common-block-item, 103
common-block-object, 103
common-directive, 527
common-stmt, 103
compilation-file, 20

Copyright © 1989–1994 Thinking Machines Corporation

complex-literal-constant, 28
computed-goto-stmt, 156
connect-spec, 236
  (ACCESS), 238
  (ACTION), 241
  (BLANK), 240
  (DELIM), 242
  (FILE), 237
  (FORM), 239
  (PAD), 242
  (POSITION), 241
  (READONLY), 240
  (RECL), 239
  (STATUS), 238
-constant
  binary, 25
  boz-literal, 25
  char-literal, 29
  complex-literal, 28
  double-precision-complex-literal, 28
  double-precision-real-literal, 27
  hex, 25
  integer-literal, 24
  literal, 24
  logical-literal, 30
  named, 72
  named-constant-def, 58
  octal, 25
  real-literal, 26
  single-precision-complex-literal, 28
  single-precision-real-literal, 26
constant, 72
-construct
  action-terminated-loop, 144
  block-if, 135
  block-loop, 140
  case, 137
  executable, 18
  execution-part, 18, 134
  loop, 140
  nonblock-loop, 144
  shared-termination-loop, 146
  where, 122
continue-stmt, 159
control-edit-desc, 274
cycle-stmt, 148

D

d (decimal field width), of a data edit descriptor, 260
data-attr-entity-decl, 52
data-attr-spec-list, 52
data-edit-desc, 260
data-implied-do, 113
data-implied-do-control, 113
data-implied-do-object, 113
data-or-dimension-spec, 54
data-stmt, 111
*data-stmt-objec*t, 111
data-stmt-set, 111
data-stmt-value, 111
deallocate-stmt, 69
-decl
  char-entity, 45
  data-attr-entity, 52
  entity, 39, 41, 49, 50
  intent-attr-entity, 55
  logical-entity, 45
  num-entity, 42
  parameter-attr-entity, 51
  save-attr-entity, 54
  type-decl, 39, 41
  type-decl-stmt
    (ALLOCATABLE-attributed), 56
    (attributed), 48
    (CHARACTER), 45, 48
    (DATA-attributed), 52
    (INTENT-attributed), 54
    (LOGICAL), 44
    (numeric), 42
    (PARAMETER-attributed), 51
    (POINTER-attributed), 56
    (SAVE-attributed), 53
declaration, 17
default-len, 48
default-length, 46
deferred-shape-array-spec, 36, 56, 60, 61
detailed-axis-descriptor, 516
digit, 7

Copyright © 1989–1994 Thinking Machines Corporation

dimension-attr-spec-list, 50
dimension-stmt, 57
directive, 505
dollar-sign, 7
double-precision-complex-literal-constant, 28
double-precision-exponent, 27
double-precision-real-literal-constant, 27
dummy-arg, 162, 167

E

e (exponent field width), of a data edit descriptor, 260
edit-descriptor, 258
edit-descriptor-list, 257
end-action-stmt, 19
endfile-stmt, 245
ending-point, 73
entity-decl, 39, 41, 49, 50
entry-stmt, 166
equivalence-object, 106
equivalence-set, 106
equivalence-stmt, 106
executable-construct, 18
executable-stmt, 18
execution-part, 18
execution-part-construct, 18, 134
exit-stmt, 147
explicit-shape-array-spec, 33
explicit-shape-spec, 33, 37, 68, 103
-expr
  case, 137
  char, 92
  logical, 95
  mask, 121
  num, 90
  relational, 93
  specification, 100
  vector-integer, 81
expr, 71
external-function-subprogram, 163
external-stmt, 184
external-subroutine-subprogram, 162
external-unit-identifier, 205, 207, 213, 215

F

file-positioning-stmt, 244
forall-assignment, 128
forall-stmt, 127
forall-triplet-spec, 127
format-identifier
  (formatted direct access), 225, 227
  (formatted sequential internal), 217, 219
  (formatted sequential), 205, 207
format-specification, 257
format-stmt, 258
function-interface-block, 175
function-reference
  (external), 170
  (intrinsic), 172

G

goto-stmt, 155

H

hex-constant, 25
hex-digit, 26

I

imaginary-part, of a *complex-literal-constant*, 28
implicit-spec, 61
implicit-stmt, 61
include-line, 11
index-value, 518
index-variable, (of a loop-construct), 140
index-variable-name
  of a `DATA` statement, 113
  of a `FORALL` statement, 127
inner-shared-loop-body, 146
input-item, 203, 205, 210, 213, 217, 221, 225, 229
input-output-stmt
  (auxiliary), 235
  (file), 189
inquire-stmt, 246

Copyright © 1989–1994 Thinking Machines Corporation

inquiry-spec, 247
inquiry-spec
(ACCESS), 250
(ACTION), 254
(BLANK), 253
(DELIM), 254
(DIRECT), 251
(EXIST), 249
(FILE), 248
(FORM), 251
(FORMATTED), 251
(IOSTAT), 253
(NAME), 250
(NAMED), 250
(NEXTREC), 252
(NUMBER), 249
(OPENED), 249
(PAD), 254
(POSITION), 253
(RECL), 252
(SEQUENTIAL), 250
(UNFORMATTED), 252
(UNIT), 248
integer-literal-constant, 24
intent-attr-entity-decl, 55
intent-attr-spec-list, 54
intent-spec, 55, 60
intent-stmt, 59
interface-block, 175
internal-file-spec, 197
intrinsic-stmt, 184
io-control-spec, 196
(END), 201
(ERR), 201
(FMT), 198
(formatted direct access), 225, 227
(formatted sequential internal), 217, 219
(formatted sequential), 205, 207
(IOSTAT), 202
(list-directed external), 213, 215
(list-directed internal), 221, 223
(NML), 199
(REC), 200
(unformatted direct access), 229, 231
(unformatted sequential), 210, 211
io-control-spec (*cont'd*)
(UNIT), 197
io-implied-do, 203
io-implied-do-control, 203
io-item, 203

K

k (scale factor), of a control edit descriptor, 274
keyword, 172
kind-selector, 39

L

label, 12, 155
layout-directive, 511, 516
layout-spec, 511, 516
letter, 7
-list, 52, 54
actual-arg, 169, 170
actual-keyword-arg, 172
data-attr-spec, 52
dimension-attr-spec, 50
dummy-arg-name, 161
edit-descriptor, 257
intent-attr-spec, 54
save-attr-spec, 54
literal-constant, 24
log-b-op, 96
log-u-op, 96
logical-entity-decl, 45
logical-expr, 95
logical-if-stmt, 135
logical-literal-constant, 30
logical-operation, 95
logical-primary, 96
logical-variable, 96
loop-body, 144
loop-construct, 140
loop-control, 141
loop-control-or-while, 140, 144
loop-termination, 140
loop-termination-action-stmt, 145
loop-termination-shared-stmt, 146

Version 2.2, October 1994
Copyright © 1989–1994 Thinking Machines Corporation

lower-bound, 33, 35, 37

M

m (minimum field width), of a data edit descriptor, 260
main-program, 20
mask-expr, 121

N

n (multiplier), in a character literal edit descriptor, 283
n (position number), of a position-edit-descriptor, 275
name, 8
named-constant, 72
named-constant-def, 58
namelist-object, 63
namelist-stmt, 63
nonblock-loop-construct, 144
num-b-op, 91
num-entity-decl, 42
num-expr, 90
num-operation, 90
num-primary, 90
num-type-spec, 42
num-u-op, 91

O

octal-constant, 25
offset-value, 518
open-stmt, 236
operation, 83
output-item, 203, 208, 212, 215, 219, 223, 227, 231

P

parameter-attr-entity-decl, 51
parameter-attr-spec, 51
parameter-stmt, 58
parent-string, 73
pause-stmt, 159
pointer-attr-spec, 56
pointer-stmt, 61
position-edit-desc, 275
position-spec, 244
primary, 71
print-stmt, 195
  (formatted sequential), 207
  (list-directed external), 215
program-unit, 15

R

r (repeat specification), in a format specification, 258
read-stmt, 195
  (formatted direct access), 225
  (formatted sequential internal), 217
  (formatted sequential), 205
  (list-directed external), 213
  (list-directed internal), 221
  (unformatted direct access), 229
  (unformatted sequential), 210
real-exponent, 26
real-literal-constant, 26
real-part, of a *complex-literal-constant*, 28
rel-op, 94
rel-operation, 94
relational-expr, 93
repeat-factor, 111
return-stmt, 185
rewind-stmt, 246

S

save-attr-entity-decl, 54
save-attr-spec-list, 54
save-or-data-spec, 50
save-or-dimension-spec, 52
save-stmt, 58
saved-object, 58
scalar-int-initialization-expression, 24
section-subscript, 76
shared-termination-loop-construct, 146
sign, 27
sign-edit-desc, 279
single-precision-complex-literal-constant, 28

Copyright © 1989–1994 Thinking Machines Corporation

single-precision-real-literal-constant, 26
source-spec, 518
special-character, 8
specification-expr, 100
specification-part, 16
specification-part-stmt, 16
specification-stmt, 17
starting-point, 73
stat-variable, 68
-stmt
  action, 19
  allocatable, 60
  allocate, 67
  arithmetic-if, 158
  assign, 156
  assigned-goto, 157
  assignment, 118
  backspace, 245
  call, 169
  close, 242
  common, 103
  computed-goto, 156
  continue, 159
  cycle, 148
  data, 111
  data-stmt-object, 111
  data-stmt-set, 111
  data-stmt-value, 111
  deallocate, 69
  dimension, 57
  end-action, 19
  endfile, 245
  entry, 166
  equivalence, 106
  executable, 18
  exit, 147
  external, 184
  file-positioning, 244
  forall, 127
  format, 258
  goto, 155
  implicit, 61
  input-output
    (auxiliary), 235
    (file), 189
-stmt (*cont'd*)
  inquire, 246
  intent, 59
  intrinsic, 184
  logical-if, 135
  loop-termination-action, 145
  loop-termination-shared, 146
  namelist, 63
  open, 236
  parameter, 58
  pause, 159
  pointer, 61
  print, 195
    (formatted sequential), 207
    (list-directed external), 215
  read, 195
    (formatted direct access), 225
    (formatted sequential internal), 217
    (formatted sequential), 205
    (list-directed external), 213
    (list-directed internal), 221
    (unformatted direct access), 229
    (unformatted sequential), 210
  return, 185
  rewind, 246
  save, 58
  specification, 17
  specification-part, 16
  stmt-function, 165
  stop, 159
  type-decl
    (ALLOCATABLE-attributed), 56
    (attributed), 48
    (CHARACTER), 45, 48
    (DATA-attributed), 52
    (INTENT-attributed), 54
    (LOGICAL), 44
    (numeric), 42
    (PARAMETER-attributed), 51
    (POINTER-attributed), 56
    (SAVE-attributed), 53
  type-decl-stmt, 39, 41
  where, 121
  write, 195
    (formatted direct access), 227

Version 2.2, October 1994
Copyright © 1989–1994 Thinking Machines Corporation

-stmt (*cont'd*)
write (*cont'd*)
(formatted sequential internal), 219
(formatted sequential), 207
(list-directed external), 215
(list-directed internal), 223
(unformatted direct access), 230
(unformatted sequential), 211
stmt-function-stmt, 165
stop-code, 159
stop-stmt, 159
stride, 77, 81
subroutine-interface-block, 175
subscript, 74, 76, 81
subscript-triplet, 76
substring-designator, 73
substring-range, 73

T

target-axis-spec, 518
target-spec, 518
type-decl-stmt, 39, 41
(ALLOCATABLE-attributed), 56
(attributed), 48
(CHARACTER), 45, 48
(DATA-attributed), 52
(INTENT-attributed), 54
(LOGICAL), 44
(numeric), 42
(PARAMETER-attributed), 51
(POINTER-attributed), 56
(SAVE-attributed), 53
type-spec, 39, 41
(DIMENSION-attributed), 50

U

u-op (unary operator), 84
underscore, 7
unit-number, 197
upper-bound, 33, 37

V

variable, 73
variable-array-element-designator, 73
variable-array-section, 73
variable-substring-designator, 73
vector-integer-expr, 77, 81

W

w (total field width), of a data edit descriptor, 260
weight, 511
where-assignment, 121
where-body, 122
where-construct, 122
where-stmt, 121
write-stmt, 195
(formatted direct access), 227
(formatted sequential internal), 219
(formatted sequential), 207
(list-directed external), 215
(list-directed internal), 223
(unformatted direct access), 230
(unformatted sequential), 211

Copyright © 1989–1994 Thinking Machines Corporation