Index of Names and Concepts

An italic page number indicates a defining reference.

Symbols

. (period), meaning .FALSE., 317
' (apostrophe), character literal constant edit descriptor, 284
→ (arrow), meaning "evaluates exactly to", 318
⇒ (double arrow)
  meaning "evaluates approximately to", 318
  meaning "is passed to", 496
[] (italic brackets) in syntax rules, to enclose optional items, xix
[] (brackets), to delimit array constructors, 81
♦ (diamond), in syntax rules, to introduce constraints, xix
. . . (ellipsis) in syntax rules, to indicate repeated items, xix
! (exclamation), beginning a comment line, 10
• (small bullet), in syntax rules, to introduce alternatives, xix
: (colon), control edit descriptor, 278
$ (dollar)
  control edit descriptor, 278
  in compiler directives, 505
  in names, 9
+ (addition operator), 24, *84*
+ (numeric identity operator), 24, *84*
− (numeric negation operator), 24, *84*
− (subtraction operator), 24, *84*
* (asterisk), in column position 1, 10
* (multiplication operator), 24, *84*
** (exponentiation operator), 24, *84*
/ (division operator), 24, *84*
/ (slash), control edit descriptor, 277
// (concatenation operator), 29, *84*
/= (not equal to operator), *84*
== (equal to operator), *84*
< (less than operator), *84*
<= (less than or equal to operator), *84*
<> (not equal to operator), *84*
> (greater than operator), *84*
>= (greater than or equal to operator), *84*
_ (underscore), in names, 9

Numbers

64-bit integer type, support for, 24

A

A, character edit descriptor, 273
ABS intrinsic function, *319*
ACCESS= specifier
  in INQUIRE statement, 250
  in OPEN statement, 238
ACOS instrinsic function, *320*
ACTION= specifier
  in INQUIRE statement, 254
  in OPEN statement, 241
actual arguments, 161, 305, 314
  pointers as, 179

Copyright © 1989−1994 Thinking Machines Corporation

AIMAG intrinsic function, *321*
AINT intrinsic function, *322*
ALIGN compiler directive, 506, *518*
ALL intrinsic function, *324*
allocatable arrays, 65
  ALLOCATED function, 67
  allocation status, 67
  declaring, 65
ALLOCATABLE attribute, *56*
ALLOCATABLE statement, *60*
ALLOCATE statement, *67*
ALLOCATED intrinsic function, 67, *326*
.AND.
  bitwise conjunction operator, *84*, *98*
  logical conjunction operator, *84*
ANINT intrinsic function, *327*
ANY intrinsic function, *329*
argument association, 178
  restrictions, 181
  with alternate return indicators, 181
  with dummy objects, 179
  with dummy procedures, 180
argument-passing conventions
  by descriptor, 496
  by reference, 496
  temporaries, 496
arguments, passing arrays as, 496
ARRAY attribute, 49, 50
array constructors. *See* arrays, constructors
array element ordering, *75*
array sections. *See* arrays, sections
arrays
  actual arguments, 35, 37, 38
  adjustable, *34*
  allocatable, 32, 65
  assumed-shape, 35, 303
  assumed-size, 37, 303
  automatic, 32, *34*
    prohibited in main program, 20
  canonical layout of, 508
  CM arrays, 4, 489
  common, 502
  conformable, *32*, 508
  constructors, 81
  declaring, 32, 50
arrays (*cont'd*)
  deferred-shape, 36
  defined, 31
  descriptors, 496
  dimension bounds, 32, 34
  dummy arguments, 32, 54
  elements of, 31, 74
  explicit-shape, 33, 303
  extent of, 31, 34
  front-end, 4, 489, 511, 513
  geometries of, 507
  homes, 489
  in expressions, 32, 74
  layout, 496, 502
    assumed-layout, 513
    block layout, 509
    communications weight, 512
    home, 489
    ordering, 512
    parallel dimensions, 509, 512
    serial dimensions, 509, 512
    serial ordering, 509
  local, 34
  named, 31, 303
  nonsequence, 183
  operations, 31
  ordering of elements, 75
  passing as arguments, 496
  pointers. *See* pointers
  rank limit, 31
  rank of, 38
  sections, 31, 76
  sequence, 183
  shape of, 31
  size of, 31, 37
  specifiers, 32
  subarrays, 31
  subscript triplets, 77
  subscripts, 74
  types of, 31
  vector-valued subscripts, 79
  whole, 32, 303
    contexts of use, 303
  zero-sized, 34, 117, 324, 329, 347, 417, 426, 442, 457, 475, 478

Version 2.2, October 1994
Copyright © 1989–1994 Thinking Machines Corporation

ASIN intrinsic function, *331*
ASSIGN statement, *156*
assignment, 118
  execution of, 119
  masked, 121
  of arrays, 118
  of conformable objects, 118
  order of execution, 123
ASSOCIATED intrinsic function, 67, *332*
association
  See also storage association
  and scope, 297
  argument association, 178
assumed-layout, dummy arrays, 513
ATAN intrinsic function, *333*
ATAN2 intrinsic function, *334*
attributes
  ALLOCATABLE, *56*
  ARRAY, 49, 50
  DATA, 34, 49, *52*
  defined, 31
  DIMENSION, *50*, 57
  in type declarations, 48
  INTENT, 49, *54*, 161
  PARAMETER, 49, *51*
  POINTER, *56*
  rank, 31
  SAVE, 34, 49, *53*
  specifying, 31, 40, 48, 57
  type, 31

B

B, integer edit descriptor, 262
BACKSPACE statement, *245*
Backus-Naur syntax form, xviii
BIT_SIZE intrinsic function, *336*
BLANK= specifier
  in INQUIRE statement, 253
  in OPEN statement, 240
BN and BZ, blank interpretation edit descriptors, 282
branching statements. *See* statements, branching
BTEST intrinsic function, *337*

C

C, in column position 1, 10
CALL statement, 162, *169*
canonical layout (of arrays), 508
CASE construct, *137*
case insensitivity, 8
CEILING intrinsic function, *339*
CHAR intrinsic function, *340*
CHARACTER keyword, 29
character set, 7
character storage unit, *102*
character string, 29
  substring, 73
CLOSE statement, *242*
CM arrays. *See* arrays
CM Fortran
  and DOD military standard, 2
  and Fortran 77, 1, 305
  and Fortran 90, 1, 2, 305
  execution model. *See* execution model
CMPLX intrinsic function, *341*
comment line, 10
common, named vs. blank, 105
common blocks, 103
  and compiler directives, 515
  arrays in, 502
  functions altering variables in, 172
  in SAVE statements, 59
  initializing data in, 114
  named, 114
COMMON compiler directive, *527*
COMMON statement, *103*
communication mechanisms, 5, 498
compiler directives, 505
  $ character in, 505
  ALIGN, 506, *518*
  blanks in, 506
  comments in, 506
  COMMON, *527*
  continuation lines, 506
  form of, 505
  LAYOUT, 506, *511*
  LAYOUT (detailed), *516*
COMPLEX keyword, 28

Copyright © 1989–1994 Thinking Machines Corporation

conformable objects, 32, 87
CONJG intrinsic function, *343*
constants. *See* literal constants
constructs, 11
  block, 134
  CASE, *137*
  indentation of, 12
  loops. *See* loop constructs
  WHERE, *122*
continuation line, 10
CONTINUE statement, 140, *159*
control edit descriptors, 274
  blank interpretation, 282
  colon, 278
  dollar, 278
  position, 275
  scale factor, 280
  sign, 279
  slash, 277
COS intrinsic function, *344*
COSH intrinsic function, *345*
COUNT intrinsic function, *346*
CSHIFT intrinsic function, *348*
CYCLE statement, 141, *148*

D

D, exponential notation edit descriptor, 267
DATA attribute, 34, 49, *52*
data edit descriptors, 260
  character, 273
  complex, 264
  integer, 261
  integer (binary), 262
  integer (hexadecimal), 262
  integer (octal), 262
  logical, 271
  numeric, 261
  real, 264
data formatting, 257
  See also FORMAT statement
  and format reversion, 286
  and interaction with I/O list, 286
  list-directed, 287
  under a format specification, 257
DATA statement, 34, *111*
data types
  and literal constants, 24
  character, 29, 38, 45
  complex, 28, 43
  declaring, 39, 42
  double-precision complex, 28, 43
  double-precision real, 26, 43
  explicit, 31, 40
  implicit, 31
  integer, 24, 43
  logical, 30, 44
  nonnumeric, 23
  numeric, 23, 24, 42
  real, 26
  single-precision real, 43
  supported in CM Fortran, 23
DATE_AND_TIME intrinsic subroutine, *352*
DBLE intrinsic function, *354*
DCMPLX intrinsic function, *355*
DEALLOCATE statement, *69*
DELIM= specifier
  in INQUIRE statement, 254
  in OPEN statement, 242
delimiters, enclosing lexical tokens, 9
descriptors. *See* arrays, descriptors
DIAGONAL intrinsic function, *356*
DIGITS intrinsic function, *358*
DIM intrinsic function, *359*
DIMENSION attribute, *50*, 57
DIMENSION statement, *57*
DIRECT= specifier, in INQUIRE statement, 251
directives, compiler. *See* compiler directives
DLBOUND intrinsic function, *398*
DO (block) construct, *141*
DO (implied in I/O), 204
DO (nonblock) construct, 144
DO TIMES (block) construct, *142*
DO WHILE (block) construct, *143*
DOT_PRODUCT intrinsic function, *360*
DOTPRODUCT intrinsic function. *See* DOT_PRODUCT intrinsic function
DOUBLE COMPLEX keyword, 28

Version 2.2, October 1994
Copyright © 1989–1994 Thinking Machines Corporation

DOUBLE PRECISION keyword, 26
DPROD intrinsic function, *362*
DSHAPE intrinsic function. *See* SHAPE intrinsic function
DSIZE intrinsic function. *See* SIZE intrinsic function
DUBOUND intrinsic function. *See* UBOUND intrinsic function
dummy arguments, 161, 174
  pointers as, 180
dummy procedures, 161

E

E, exponential notation edit descriptor, 267
elemental functions. *See* functions, elemental
ELSE IF statement, 136
ELSE statement, 136
ELSEWHERE statement, *122*
END statement, *19*
ENDFILE statement, *245*
ENTRY statement, 21, *166*
EOSHIFT intrinsic function, *363*
EPSILON intrinsic function, *369*
.EQ. (equal to operator), *84*
EQUIVALENCE statement, *105*
.EQV.
  bitwise equivalence operator, *84*, *98*
  logical equivalence operator, 30, *84*
ERR= specifier, in INQUIRE statement, 253
executable statement. *See* statements
EXIST= specifier, in INQUIRE statement, 249
EXIT statement, 141, *147*
EXP intrinsic function, *370*
explicit interfaces, 497
explicit typing, of names beginning with underscore, 9
EXPONENT intrinsic function, *371*
expressions
  array sections in, 77
  bitwise logical, 98
  character, 92
  conformable objects in, 87
expressions (*cont'd*)
  constant, 72, 99
  logical, 95
  numeric, 90
  parenthesized, 90
  primary, 71
  relational, 93
  shape of, 84
  specification, 100
  type of, 72, 89
  variable, 72
external files, connecting a unit to, 235
external procedure, 162
EXTERNAL statement, *184*, 306

F

F, decimal edit descriptor, 264
F, abbreviation for .FALSE., 317
FILE= specifier
  in INQUIRE statement, 248
  in OPEN statement, 237
files, external, 189
  direct access, 191
  end-of-file condition, 190
  named, 189
  position of, 191, 235
  sequential access, 190
  sequential data transfer, 205
files, internal, 193
  properties of, 193
FIRSTLOC intrinsic function, *372*
FLOOR intrinsic function, *374*
FORALL statement, *127*
FORM= specifier
  in INQUIRE statement, 251
  in OPEN statement, 239
format specification, 257
FORMAT statement, syntax of, *258*
FORMATTED= specifier, in INQUIRE statement, 251
Fortran 77, and CM Fortran, 1, 9, 305
Fortran 90, and CM Fortran, 1, 2, 9, 305
FRACTION intrinsic function, *375*
front-end arrays. *See* arrays

Copyright © 1989–1994 Thinking Machines Corporation

function reference, in IF or WHERE statements, 172
FUNCTION statement, *163*
functions
  array-valued, 164
  elemental, 162, 173, 305
  interface of, 163
  intrinsic. *See* intrinsic functions
  invoking, 170
  references. *See* functions, invoking
  statement functions, 162, 165

G

G, generalized numeric edit descriptor, 270
.GE. (greater than or equal to operator), *84*
general (router) communication, *5*, 500
geometries, 507
  communications weight of axes, 508
  element ordering of axes, 508
  locality of axes, 508
  size of axes, 508
global communication, *5*
global variables, *101*
GO TO (assigned) statement, *156*
GO TO (computed) statement, *155*
GO TO statement, *155*
grid (NEWS) communication, *5*
.GT. (greater than operator), *84*

H

H, Hollerith constant edit descriptor, 284
character literal edit descriptors, 283
  constants, 284
  Hollerith constants, 284
homes. *See* arrays, homes
HUGE intrinsic function, *376*

I

I, integer edit descriptor, 261
I/O, run-time status codes, 233
I/O control specifiers, 196
  and data edit descriptors, 196
I/O control specifiers (*cont'd*)
  END=, *201*, 232
  ERR=, *201*, 232
  FMT=, *198*, 259
  IOSTAT=, *202*, 232
  REC=, *200*
  UNIT=, *197*
I/O editing. *See* data edit descriptors, character literal edit descriptors, and control edit descriptors
I/O statements. *See* statements, data transfer; READ, PRINT, and WRITE statements
IAND intrinsic function, *377*
IBCLR intrinsic function, *379*
IBITS intrinsic function, *380*
IBSET intrinsic function, *382*
ICHAR intrinsic function, *383*
IEOR intrinsic function, *384*
IF (arithmetic) statement, *158*
IF (block) construct, *135*
IF (logical) statement, *135*
IF–THEN statement, 136
implicit interfaces, 496
IMPLICIT statement, 31, *61*
implied DO control, 204
  in a DATA statement, 113
  in an I/O statement, 204
INCLUDE line, *11*
INCLUDE lines, with compiler directives, 506
INDEX intrinsic function, *386*
initial line, 10
INQUIRE statement, *246*
INT intrinsic function, *387*
integer type, 64-bit, support for, 24
INTEGER*4 keyword, 24
INTEGER*8 keyword, 24
INTEGER*8 type, support for, 24
INTENT attribute, 49, *54*, 161
INTENT statement, *59*
interface, 162
interface blocks, 165, *175*, 497
  as scoping units, 297

Copyright © 1989–1994 Thinking Machines Corporation

interface blocks (*cont'd*)
order of statements, 177
interfaces to procedures
defined, *174*
explicit, 177, 497
implicit, 177, 496
intrinsic functions
(specifications, arranged alphabetically), 319–394
array construction, 311
DIAGONAL, *356*
MERGE, *419*
PACK, *436*
REPLICATE, *456*
RESHAPE, *458*
SPREAD, *474*
UNPACK, *487*
array inquiry, 311
LBOUND, *398*
RANK, *452*
SHAPE, *466*
SIZE, *471*
UBOUND, *485*
array location, 312
FIRSTLOC, *372*
LASTLOC, *396*
MAXLOC, *413*
MINLOC, *422*
PROJECT, *444*
array manipulation, 312
CSHIFT, *348*
EOSHIFT, *363*
TRANSPOSE, *484*
array reduction, 310
ALL, *324*
ANY, *329*
COUNT, *346*
MAXVAL, *416*
MINVAL, *425*
PRODUCT, *441*
SUM, *477*
bit-level, 309
BTEST, *337*
IAND, *377*
IBCLR, *379*
intrinsic functions (*cont'd*)
bit-level (*cont'd*)
IBITS, *380*
IBSET, *382*
IEOR, *384*
IOR, *389*
ISHFT, *391*
ISHFTC, *393*
LEADZ, *400*
NOT, *435*
POPCNT, *438*
POPPAR, *439*
character, 308
CHAR, *340*
ICHAR, *383*
INDEX, *386*
LEN, *402*
LGE, *403*
LGT, *404*
LLE, *405*
LLT, *406*
defined, 162, 305
elemental, 305
floating-point manipulation, 310
EXPONENT, *371*
FRACTION, *375*
NEAREST, *432*
RRSPACING, *461*
SCALE, *462*
SET_EXPONENT, *465*
SPACING, *473*
inquiry, 305
ALLOCATED, 67, *326*
ASSOCIATED, *332*
BIT_SIZE, *336*
kind, 308
KIND, *395*
SELECTED_INT_KIND, *463*
SELECTED_REAL_KIND, *464*
mathematical, 307
ACOS, *320*
ASIN, *331*
ATAN, *333*
ATAN2, *334*
COS, *344*

Copyright © 1989–1994 Thinking Machines Corporation

intrinsic functions (*cont'd*)
mathematical (*cont'd*)
COSH, *345*
EXP, *370*
LOG, *407*
LOG10, *408*
SIN, *469*
SINH, *470*
SQRT, *476*
TAN, *481*
TANH, *482*
matrix multiplication, 310
DOT_PRODUCT, *360*
MATMUL, *409*
numeric, 306
ABS, *319*
AIMAG, *321*
AINT, *322*
ANINT, *327*
CEILING, *339*
CMPLX, *341*
CONJG, *343*
DBLE, *354*
DCMPLX, *355*
DIM, *359*
DPROD, *362*
FLOOR, *374*
INT, *387*
MAX, *411*
MIN, *420*
MOD, *428*
MODULO, *429*
NINT, *433*
REAL, *453*
SIGN, *468*
numeric inquiry, 309
DIGITS, *358*
EPSILON, *369*
HUGE, *376*
MAXEXPONENT, *412*
MINEXPONENT, *421*
PRECISION, *440*
RADIX, *447*
RANGE, *450*
TINY, *483*
intrinsic functions (*cont'd*)
specific names of, 314
transformational, 305
vector multiplication, 310
DOT_PRODUCT, *360*
MATMUL, *409*
intrinsic procedures. *See* intrinsic functions
INTRINSIC statement, *184*
intrinsic subroutines, 313
DATE_AND_TIME, *352*
MVBITS, *430*
RANDOM_NUMBER, *448*
RANDOM_SEED, *449*
SYSTEM_CLOCK, *480*
IOR intrinsic function, *389*
IOSTAT= specifier, in INQUIRE statement, 253
ISHFT intrinsic function, *391*
ISHFTC intrinsic function, *393*

K

keywords
as lexical tokens, 8
CHARACTER, 29
COMPLEX, 28
DOUBLE COMPLEX, 28
DOUBLE PRECISION, 26
in intrinsic function calls, 172
INTEGER*4, 24
INTEGER*8, 24
LOGICAL, 30
not reserved words, 8
REAL, 26
statement keywords, 8
KIND, scalar integer constant expressions for indicating, 40
KIND intrinsic function, *395*
kind type, 309
kind type parameter, 44

L

L, logical edit descriptor, 271
labeled lines. *See* statements, labels

Version 2.2, October 1994
Copyright © 1989–1994 Thinking Machines Corporation

LASTLOC intrinsic function, *396*
LAYOUT (detailed) compiler directive, *516*
LAYOUT compiler directive, 506, *511*
LBOUND intrinsic function, *398*
.LE. (less than or equal to operator), *84*
LEADZ intrinsic function, *400*
LEN intrinsic function, *402*
LGE intrinsic function, *403*
LGT intrinsic function, *404*
line, INCLUDE, *11*
lines, 10
  comment, 10
  continuation, 10
  initial, 10
  labeled. *See* statements, labels
list-directed
  data formatting, 287
  input, 288
  input, of null fields, 290
  output, 291
literal constants, 24, 72
  and named constants, 72
  character, 29
  complex, 28
  double-precision real, 27
  integer, 25
  logical, 30
  real, 27
  typed, 44
LLE intrinsic function, *405*
LLT intrinsic function, *406*
location of objects in memory, control over, 101
LOG intrinsic function, *407*
LOG10 intrinsic function, *408*
LOGICAL keyword, 30
loop constructs
  action-terminated, 144
  block, 140
  DO (block), *141*
  DO TIMES (block), *142*
  DO WHILE (block), *143*
  execution of, 149
  nonblock, 144
  shared-termination, 146
.LT. (less than operator), *84*

M

MATMUL intrinsic function, *409*
MAX intrinsic function, *411*
MAXEXPONENT intrinsic function, *412*
MAXLOC intrinsic function, *413*
MAXVAL intrinsic function, *416*
MERGE intrinsic function, *419*
MIN intrinsic function, *420*
MINEXPONENT intrinsic function, *421*
MINLOC intrinsic function, *422*
MINVAL intrinsic function, *425*
MOD intrinsic function, *428*
MODULO intrinsic function, *429*
MVBITS intrinsic subroutine, *430*

N

NAME= specifier, in INQUIRE statement, 250
named constants, 72
NAMED= specifier, in INQUIRE statement, 250
NAMELIST statement, *63*
names
  as lexical tokens, 8
  beginning with underscore, 9
  case-insensitive, 8
  containing a $ character, 9
  identifying program components, 8
  scope of, 298
  uses of whole array names, 303
.NE. (not equal to operator), *84*
NEAREST intrinsic function, *432*
.NEQV.
  bitwise nonequivalence operator, *84*, *98*
  logical nonequivalence operator, 30, *84*
NEWS addresses, 507
NEWS communication, *5*
NEXTREC= specifier, in INQUIRE statement, 252
NINT intrinsic function, *433*

Copyright © 1989–1994 Thinking Machines Corporation

.NOT.
  bitwise complementation operator, *84*, *98*
  logical negation operator, 30, *84*
NOT intrinsic function, *435*
notation conventions, xviii, 317
NUMBER= specifier, in INQUIRE statement, 249
numeric storage unit, *102*

O

O, integer edit descriptor, 262
OPEN statement, *236*
OPENED= specifier, in INQUIRE statement, 249
operators
  addition, 24, *84*
  associativity, 89
  bitwise complementation, *84*, *98*
  bitwise conjunction, *84*, *98*
  bitwise equivalence, *84*, *98*
  bitwise exclusive disjunction, *84*, *98*
  bitwise inclusive disjunction, *84*, *98*
  bitwise nonequivalence, *84*, *98*
  concatenation, 29, *84*
  division, 24, *84*
  equal to, *84*
  exponentiation, 24, *84*
  greater than, *84*
  greater than or equal to, *84*
  less than, *84*
  less than or equal to, *84*
  logical conjunction, 30, *84*
  logical equivalence, 30, *84*
  logical exclusive disjunction, 30, *84*
  logical inclusive disjunction, 30, *84*
  logical negation, 30, *84*
  logical nonequivalence, 30, *84*
  multiplication, 24, *84*
  not equal to, *84*
  numeric, 91
  numeric identity, 24, *84*
  numeric negation, 24, *84*
  precedence, 87
operators (*cont'd*)
  relational, 30, 93
  subtraction, 24, *84*
  supported in CM Fortran, 83
  with characters, 92
  with constants, 99
  with integers, 98
  with logicals, 95
.OR.
  bitwise inclusive disjunction operator, *84*, *98*
  logical inclusive disjunction operator, 30, *84*
order of statements
  in a block data program unit, 115
  in a program unit, 21
  in an interface block, 177

P

P, scale factor edit descriptor, 280
PACK intrinsic function, *436*
PAD= specifier
  in INQUIRE statement, 254
  in OPEN statement, 242
PARAMETER attribute, 49, *51*
PARAMETER statement, *58*
PAUSE statement, *159*
POINTER attribute, *56*, 66
POINTER statement, *61*, 66
pointers, 65
  allocating, 67
  allocation status, 67
  as actual arguments, 179
  as dummy arguments, 180
  ASSOCIATED function, 67
  deallocating, 69
  declaring, 65
  in common, 65
POPCNT intrinsic function, *438*
POPPAR intrinsic function, *439*
POSITION= specifier
  in INQUIRE statement, 253
  in OPEN statement, 241
PRECISION intrinsic function, *440*

Version 2.2, October 1994
Copyright © 1989–1994 Thinking Machines Corporation

PRINT statement, *195*
  formatted sequential, *207*
  list-directed, *215*
procedures
  defined, 161
  invoking, 168
  no recursive, 169
PRODUCT intrinsic function, *441*
program, 15
PROGRAM statement, 20
program unit, 15
  as scoping unit, 297
PROJECT intrinsic function, *444*

R

RADIX intrinsic function, *447*
RANDOM_NUMBER intrinsic subroutine, *448*
RANDOM_SEED intrinsic subroutine, *449*
RANGE intrinsic function, *450*
RANK intrinsic function, *452*
READ statement, *195*
  formatted direct access, *225*
  formatted sequential, *205*, *217*
  list-directed, *213*, *221*
  unformatted direct access, *229*
  unformatted sequential, *210*
READONLY specifier, in OPEN statement, 240
REAL intrinsic function, *453*
REAL keyword, 26
RECL= specifier
  in INQUIRE statement, 252
  in OPEN statement, 239
records
  endfile, 195
  formatted, 194
  formatted, printing of, 209
  unformatted, 194
reference
  elemental intrinsic function, 173
  function, 170
  intrinsic function, 172
  procedure, 168
  subroutine, 169
REPLICATE intrinsic function, *456*
reserved words, keywords not reserved, 8
RESHAPE intrinsic function, *458*
RETURN statement, 151, *185*
reversion, of format control, 286
REWIND statement, *246*
router communication, *5*
RRSPACING intrinsic function, *461*

S

S, SP, and SS, sign edit descriptors, 279
SAVE attribute, 34, 49, *53*
SAVE statement, 34, *58*
saved objects. *See* SAVE attribute
scalar integer constant expressions, 40
scalars
  as array elements, 31
  conformable with arrays, 32
  defined, 31
  rank of, 31
SCALE intrinsic function, *462*
scope, 297
  and the ALIGN directive, 522
  global entities, 297
  local entities, 297
  of argument keywords, 299
  of common block names, 299
  of function result variables, 299
  of statement entities, 299
  of statement labels, 300
  scoping units, 297
  statement entities, 297
SELECT CASE statement, *138*
SELECTED_INT_KIND intrinsic function, *463*
SELECTED_REAL_KIND intrinsic function, *464*
send addresses, 507
sequence association, 182
SEQUENTIAL= specifier, in INQUIRE statement, 250
SET_EXPONENT intrinsic function, *465*
SHAPE intrinsic function, *466*
shape of array, 31

Copyright © 1989–1994 Thinking Machines Corporation

shape vectors, 32
SIGN intrinsic function, *468*
SIN intrinsic function, *469*
SINH intrinsic function, *470*
SIZE intrinsic function, *471*
SPACING intrinsic function, *473*
SPREAD intrinsic function, *474*
SQRT intrinsic function, *476*
statements, 11
  action, 19
  ALLOCATABLE, *60*
  ALLOCATE, *67*
  ASSIGN, *156*
  assignment, 118
  attribute specification, 31, 57
  BACKSPACE, *245*
  blocks of, 133
  CALL, 162, *169*
  CLOSE, *242*
  COMMON, *103*
  CONTINUE, 140, *159*
  CYCLE, 141, *148*
  DATA, 34, *111*
  DEALLOCATE, *69*
  DIMENSION, *57*
  ELSE, 136
  ELSE IF, 136
  ELSEWHERE, *122*
  END, *19*
  ENDFILE, *245*
  ENTRY, 21, *166*
  EQUIVALENCE, *105*
  executable, classes of, 15
  EXIT, 141, *147*
  EXTERNAL, *184*
  file connection, 235
  file I/O, 195
  file inquiry, 246
  file positioning, 244
  FORALL, *127*
  FORMAT, *258*
  FUNCTION, *163*
  GO TO, *155*
  GO TO (assigned), *156*
  GO TO (computed), *155*
  IF (arithmetic), *158*
  IF (logical), *135*
  IF–THEN, 136
  IMPLICIT, 31, *61*
  INQUIRE, *246*
  INTENT, *59*
  INTRINSIC, *184*
  labels, 12
  NAMELIST, *63*
  nonexecutable, classes of, 16
  OPEN, *236*
  order of
    in a block data program unit, 115
    in a program unit, 21
    in an interface block, 177
  PARAMETER, *58*
  PAUSE, *159*
  POINTER, *61*
  PRINT, *195*
  PRINT (formatted sequential), *207*
  PRINT (list-directed), *215*
  PROGRAM, 20
  READ, *195*
  READ (formatted direct access), *225*
  READ (formatted sequential), *205*, *217*
  READ (list-directed), *213*, *221*
  READ (unformatted direct access), *229*
  READ (unformatted sequential), *210*
  RETURN, 151, *185*
  REWIND, *246*
  SAVE, 34, *58*
  SELECT CASE, *138*
  specification, 17
  statement function, 165
  STOP, 21, *159*
  SUBROUTINE, *162*
  type declaration, 31, 39
  WHERE, *121*
  WRITE, *195*
  WRITE (formatted direct access), *227*
  WRITE (formatted sequential), *207*, *219*
  WRITE (list-directed), *215*, *222*
  WRITE (unformatted direct access), *230*

Copyright © 1989–1994 Thinking Machines Corporation

statements (*cont'd*)
WRITE (unformatted sequential), *211*
STATUS= specifier, in OPEN statement, 238, 243
STOP statement, 21, *159*
storage assocation
of objects, 101
partial, *102*
total, *102*
storage order dependencies, of Fortran 77, 1
storage sequence, *101*
of common blocks, 104, 105
stride. *See* arrays, subscript triplets
subprogram, defined, 161
SUBROUTINE statement, *162*
subroutines, invoking, 169
subscript order value, *75*
subscripts. *See* arrays, subscripts
substrings, 73
SUM intrinsic function, *477*
syntax rules, defined, xviii
SYSTEM_CLOCK intrinsic subroutine, *480*

T

T, meaning .TRUE., 317
T, TL, and TR, position edit descriptors, 275
TAN intrinsic function, *481*
TANH intrinsic function, *482*
TINY intrinsic function, *483*
TRANSPOSE intrinsic function, *484*
triplet subscripts, 76, 77
See also arrays, sections
typed constants, 44

U

UBOUND intrinsic function, *485*
UNFORMATTED= specifier, in INQUIRE statement, 252
UNIT= specifier, in INQUIRE statement, 248
UNPACK intrinsic function, *487*

V

variables
defining the value of, 300
undefining the value of, 301
vector-valued subscripts, 79
virtual grids, 507

W

WHERE construct, *122*
WHERE statement, *121*
WRITE statement, *195*
formatted direct access, *227*
formatted sequential, *207*, *219*
list-directed, *215*, *222*
unformatted direct access, *230*
unformatted sequential, *211*

X

X, position edit descriptor, 276
.XOR.
bitwise exclusive disjunction operator, *84*, *98*
logical exclusive disjunction operator, 30, *84*

Z

Z, integer edit descriptor, 262
zero-sized arrays. *See* arrays, zero-sized

Copyright © 1989–1994 Thinking Machines Corporation