Figures

1 The CM Fortran compiler's machine model 7
2 The compiler's "two machines" output 8
3 Division of labor between CM system components 10
4 Two conformable vectors laid out on 16 processors 21
5 Two nonconformable vectors laid out on 16 processors 21
6 The CM Fortran compilation process for CM-5 with vector units 28
7 SPARC nodes model 31
8 Vector-units model without vector-length padding. 32
9 Vector-units model with vector-length padding 33
10 Nodal CM Fortran model, hostless model 35
11 Nodal Fortran 77, hostless model 36
12 Nodal CM Fortran, host/node model 38
13 Global/local model without vector-length padding. 40
14 Computing on arrays and subarrays in global/local model 41
15 CM Fortran simulator 42
16 A masked array assignment 58
17 Inversion of the mask array in a **`WHERE-ELSEWHERE`** construct 59
18 **`DO`** versus **`FORALL`** in transposing array elements (2,1) and (1,2) 155
19 An 8 x 12 array laid out on a 2 x 8 physical grid 187
20 An 8 x 12 array on 16 VUs with **`-nopadding`** 188
21 An 8 x 12 array laid out on an 8 x 2 physical grid 190
22 Two possible vector-unit numberings 191
23 Default layout of an 8 x 12 array on 16 vector units 193
24 Subgrids and physical grids for an 8 x 12 array on four nodes 194

Copyright © 1989–1994 Thinking Machines Corporation

25 Default layout of an 8 x 12 array on four nodes 195
26 On-VU and off-VU data movement for a NEWS operation along axis 2 201
27 A physical grid with processor masks of 3 and 28 206
28 Programmer's view: Global/local programming 215
29 Computing on arrays and subarrays 218
30 A 2D array and its four subarrays 227
31 A 2D array and its four subarrays 233

Version 2.2, October 1994
Copyright © 1989–1994 Thinking Machines Corporation