Index

Numbers

64-bit integers, 66

A

.a files, 56
abs, 6
as, 68
assembly files, 56
assembly language source file, keeping, 63
at command, 76

B

batch command, 76
batch mode, executing in, 76
bin directory, 62
binary search path, 62
<bitop.h>, 5
boolcmp, 6
boolcpy, 6
boolmove, 6
boolset, 6
boolsizeof, 51

C

C compiler, using other than the default, 61
.c files, 3, 56
  putting through C* compilation, 63
C*, 1
cc, 58, 68
CDPEAC function, calling, 11
CM Fortran
  calling C*, 17
  calling from C*, 13
CM libraries, calling from C*, 10
CM/AVS, 11
<cm/cmfs.h>, 49
<cm/timers.h>, 9
CM_read, 40
  example of, 47
CM_write, 40
  example of, 45
__CM5__ symbol, 72
__CM5_SPARC__ symbol, 72
__CM5_VECUNIT__ symbol, 72
CMC_alloc_io_buffer, 41
CMC_allocate_shape_from_desc, 18
CMC_call_pn_function, 11
CMC_complex_t, 19
CMC_descriptor_t, 13, 15, 18
CMC_double_complex_t, 19
CMC_free_io_buffer, 41
CMC_get_from_io_buffer, 42
CMC_pointer_mem_addr, using to pass parallel data to PN routine, 12
CMC_pointer_mem_stride, and calling PN functions, 12
CMC_read_from_io_buffer, 44
CMC_same_geometry, 18

Copyright © 1990–1995 Thinking Machines Corporation

CMC_send_to_io_buffer, 42
CMC_shape_subgrid_size, and calling PN functions, 12
CMC_unwrap_pvar, 18
CMC_wrap_pvar, 13, 15
CMC_write_to_io_buffer, 44
CMFS interface, linking for, 50
CMFS_lseek, 51
CMFS_physical_transfer_length, 53
CMFS_read_file, 50
CMFS_read_file_physical, 52
CMFS_serial_lseek, 51
CMFS_write_file, 50
CMFS_write_file_physical, 52
cmld, 68, 69
CMMD, 11
CMMD_ROOT, 66
CMSSL, 10
<cmsys/csio.h>, 40
CMX11, 11
compiler, default, 58
compiling
  changing location of temporary files, 67
  creating assembly source files, 67
  displaying steps in, 62
  getting help, 59
  turning off warnings in, 67
compiling a C* program, 2, 55
cs, 2, 55, 93–99
  +l option, 63
  -c option, 60, 69
  -cc option, 61
  -cm2 option, 58
  -cm200 option, 58
  -cm5 option, 58
  -cmdebug option, 60, 61, 81
  -cmmd_root option, 11, 66
  -cmprofile option, 61, 81
  -cmsim option, 49, 58, 79
    and libraries, 10
  -csconfig option, 65
  -D option, 60
  -dirs option, 62
  -dryrun option, 62
  -E option, 60
  -force option, 63
  -g option, 60, 81
  -help option, 59
  -I option, 60, 62
  -keep option, 63
  -L option, 60, 62
  -l option, 60
  -local option, 65
  -noansilibs option, 65
  -node option, 11, 66
  -noprintflibs option, 66
  -o option, 60
  -overload option, 66
  -P option, 60
  -pedantic option, 67
  -S option, 67, 69
  -sparc option, 60
  -temp option, 67
  -U option, 60
  -v option, 67
  -vecunit option, 60
  -verbose option, 67
  -version option, 60
  -vu option, 60
  -warn option, 67
  -Wimplicit option, 68
  -Z option, 68
  options in common with cc, 60
  symbols defined for, 72
.cs files, 1, 3
CS_AUTO_PE_FILES, 69
CS_DEFAULT_MACHINE environment variable, 59
<cscomm.h>, 5, 102–105
<csfort.h>, 5, 13, 17
<csgl.h>, 5
<csshape.h>, 5
<cstable.h>, 5
cstar-config configuration file, 64
__CSTAR__ symbol, 72
<cstimer.h>, 9

Version 7.2, May 1995
Copyright © 1990–1995 Thinking Machines Corporation

current, used in **<X11/Xlib.h>**, 7

D

deallocate_shape, 6, 18

debugging, 2
  -g or **-cmdebug** compiler option
    required for, 60

developing C* programs, 1

DJM, 76

dpas, 68

DPEAC files, 56
  keeping, 63

DPEAC function, calling, 11

E

executing C* programs, 2

F

fread
  example of, 32
  limitations of, 31
  parallel version of, 26
  performance of, 29

functions, undeclared, displaying a warning
    from compiler, 68

fwrite
  example of, 31
  limitations of, 31
  parallel version of, 26
  performance of, 29

G

global/local programming, compiling for, 65

global/local programming model, 12

global/local programs, debugging, 88

H

header files, 4
  and C* keywords, 7

I

I/O, 49
  performing, 25
  physical. *See* physical I/O
  which method to use, 25

identifiers, reserved, 4

include directory, 62

include search path, 62

intermediate files, 69
  See also **. . c** files

J

jrun, 77

jsub, 77

K

keywords
  and header files, 7
  list of C*, 4

L

ld, 68

lib directory, 62

libraries, creating, 70

library search path, 62

linking, 68
  using **+l** option for, 63

__LONG_LONG__ symbol, 72

Copyright © 1990–1995 Thinking Machines Corporation

M

make utility, 73
<math.h>, 5, 106–109
memcmp, 6
memcpy, 6
memmove, 6
memset, 6

N

NMO buffer
  allocating and freeing, 41
  creating and using, 40
  writing to and reading from, 42
NMO order, 29
NQS, 78

O

.o files, 56
object file, keeping, 63
overloading, 66

P

palloc, 6
parallel objects, visualizing in Prism, 87
parallel sockets, and **fread**, **fwrite**, 30
parallel variables, randomizing, 6
.pe files, 69
performance data, obtaining, 61
pfree, 6
physical I/O, performing, 52
PN functions, calling, 11
pndbx, using with global/local programs, 89
pointers, scalar-to-parallel, constructing, 87
prand, 6
Prism
  compiling for, 81
  debugging in, 84
  loading and executing programs in, 84
  performance analysis in, 87
  starting, 81
  using, 83
  visualizing data in, 85
psrand, 6

Q

qsub, 78

R

rand, 6
  See also **prand**
run-time libraries, names of, 68

S

.s files, 56
socket I/O, example of, 33
sparc, 72
srand, 6
  See also **psrand**
<stdarg.h>, 110–111
__STDC__ symbol, 73
<stdlib.h>, 6, 112–113
<string.h>, 6, 114
sun, 72
Sun-4, executing a C* program on, 79

T

temporary files, location of, 62

Version 7.2, May 1995
Copyright © 1990–1995 Thinking Machines Corporation

timing utility, 7

U

unix symbol, 72

V

vector units, compiling to run on, 60

W

warnings, turning off, 67

X

<X11/Xlib.h>, use of **current** in, 7

Copyright © 1990–1995 Thinking Machines Corporation