Index

Symbols

? command, 22
  and split source window, 224
#, 155
@, 28, 121
+=, 34
*****, 189
***=**, 34
/ command, 22
  and split source window, 224
<?=, 34
>, 189
>?=, 34
****, 155

A

acc, 8
adjustable arrays, printing, 81
Advice selection, 122
AIMAG intrinsic function, 33
alias, 227
alias command, 141, 155
aliases, creating, 141
ALL intrinsic function, 33
all PN set, 166, 172
ANY intrinsic function, 33
app-defaults file, 142, 151
array-section syntax, using in C* left indexes, 35
arrays, dynamic, visualizing in structure visualizers, 103
arrow keys, 14
  using to scroll through source window, 22
assembly code, displaying in split source window, 23
assign command, 107
  not available when examining node core files, 205
assigning to a variable or array, 107
attach command, 45
  and Node Prism, 182, 184
  can't be used in actions field, 61
attaching to a running process, 44
auto-attaching in Prism, 48

B

base, changing, 108
/bin/make, 128, 145
break PN set, 166, 191
breakpoints, 227
  deleting, 67, 68, 71
  in Node Prism, 190
    synchronization required for, 192
  setting, 65
    using commands to set, 68
    using the event table and **Events** menu to set, 67
    using the line-number region to set, 66
Bug Updates selection, 136, 144
bug-update files
  viewing, 136
  viewing in commands-only Prism, 218

C

C*, **-O0** compiler option, 110
C* functions, passing parallel variables to, 35
C* left indexes, using array-section syntax in, 35

Copyright © 1991–1994 Thinking Machines Corporation

C* reduction operators, using in expressions, 34
call stack, 227
  displaying, 74
  moving through, 75
cc, 8
cd command, 37
changes, where Prism stores, 146
CM documents, viewing, 134
CM Fortran
  -nodebug option, 72
  global/local programs, using Prism with, 185
CM menu, 45
CM timers, 124
  and performance analysis, 111
CM-2, 45
CM-2/200
  attaching to, 45
  cold booting, 48
  detaching from, 48
  turning safety on and off, 49
CM-2/200 users, obtaining information about, 49
CM-200, 45
cmattach command, 45, 47
CMattach selection, 46
CMAX, 24
  using Prism with, 221
CMAX mapping file, 221
cmcoldboot command, 48
CMcoldboot selection, 48
cmdetach command, 48
CMdetach selection, 48
cmf, 8
cmfinger command, 49
CMfinger selection, 49
CMMD, 157
cmmd_debug, pausing execution at, 183
CMPLX intrinsic function, 33, 93
CMPROF_N_USER_TIMERS environment variable, 111, 124
-cmprofile compiler option, 9, 66, 110
  effect on stepping, 51
CMPROFILING environment variable, 113
CMPROFILING_DATA_FILENAME environment variable, 113
CMPROFILING_EXECUTABLE_FILENAME environment variable, 113
cmps command, 11, 45, 184
cmsetsafety command, 49
CMsetsafety selection, 49
CMSSL routines, performance data for, 110
CMTS_ScalarMain, 75
CMTSD_core_pn file, 204
CMTSD_dp.pn file, 204
CMTSD_errors file, 204
CMTSD_heap.pn file, 204
CMTSD_stack.pn file, 204
CMview, 5, 134
collection command, 112, 217
Collection selection, 112
colormap visualizers, 4, 92
  changing the colors for, 150
  changing the size of the default spectral color map for, 150
  minimum and maximum values of, 95
colors, changing Prism's standard, 151
command line, 26
  using, 26
command window, 3, 227
  using, 26
commands
  adding to the tear-off region, 141
  executing from a file, 29
  issuing, 15
  issuing multiple, 26
  logging, 29
  setting up alternative names for, 141
Commands Reference selection, 133
Common Events buttons, 62, 84
compilers, supported, 8
compiling and linking, 8
  from within Prism, 128
complex numbers, 90, 97
connect command, 161
cont command, 52
  and auto-attaching, 48
  in Node Prism, 187

Version 2.0, April 1994
Copyright © 1991–1994 Thinking Machines Corporation

context, 227
  setting via **print** or **display** command, 86
Continue selection, 52
continuing execution, 52
contw command, 189
  cannot be used in event actions, 193
core command, 44
  can't be used in actions field, 61
  not available in Node Prism, 205
core files
  associating with loaded programs, 11, 44
  node, 159
    examining, 203
COUNT intrinsic function, 33
cs, 8
Ctrl-a, 15, 216
Ctrl-b, 15, 216
Ctrl-c, 14, 26, 52, 216
  ending a wait in Node Prism, 188
Ctrl-d, 15, 216
Ctrl-e, 15, 216
Ctrl-f, 15, 216
Ctrl-h, 216
Ctrl-j, 216
Ctrl-k, 15, 216
Ctrl-l, 216
Ctrl-m, 216
Ctrl-n, 27, 216
Ctrl-p, 27, 216
Ctrl-u, 15, 216
Ctrl-x, 22
Ctrl-z, 190
current execution point, returning to, 22
current file, 53, 227
  changing, 53
current function, 53, 228
  changing, 54
  changing via the **Where** graph, 198
current PN, 177
  changing, 178
current PN set, 174
  and dynamic PN sets, 176
  and variable PN sets, 177
  changing via the **Where** graph, 198
  finding out, 175
  setting, 175
current working directory, changing and printing, 37
Customize selection, 142
Customize utility, using, 142
cycle command, 179, 209
cycle PN set, 178, 209
Cycle window, 180, 209

D

data
  changing the radix of, 108
  modifying, 107
data navigator, 4, 228
  using, 88
dbx, 15
dedicated window, 28, 84
define pnset command, 170
  cannot be used in event actions, 193
Define Type selection, 30
delete command, 71, 73, 217
delete pnset command, 174
  cannot be used in event actions, 193
Delete selection, 63, 72
detach command, 45
  and Node Prism, 185
  can't be used in actions field, 61
detaching from a running process, 44
dialog boxes, 228
  using, 20
dimof, 34
disable command, 65
disconnect command, 162
display command, 85
  redirecting output to X window, 219
Display Data selection, 113
Display dialog box, 84
DISPLAY environment variable, 10
Display selection (**Debug** menu), 82
  in Node Prism, 207
display window, 228
  using, 88

Copyright © 1991–1994 Thinking Machines Corporation

displaying
  difference from printing, 80
  from the command window, 85
  from the **Debug** menu, 82
  from the event table, 84
  from the **Events** menu, 83
doc command, 218
done PN set, 166
dot notation, 34
down command, 75
Down selection, 75
DSIZE intrinsic function, 33

E

eachinst keyword, 61
eachline keyword, 61
edit command, 127
edit geometry, 144
Edit selection, 127, 144, 149, 224
editing source code, 127
editor, specifying default, 149
EDITOR environment variable, 127, 144
elevator, 20
email command, 136
Email selection, 136, 144
enable command, 65
environment variables, setting and displaying, 38
error bell, 144
error messages, specifying window for, 149
error PN set, 166
error window, 144
errors, Prism's behavior after, 154
Esc key, 14
eval pnset command, 171, 177, 192
event list, 60, 71, 228
event table, 228
  description of, 59
  using, 59
Event Table selection, 59
events, 228
  adding, 62
  and deleted PN sets, 193
  deleting, 63
  disabling, 64
  editing, 63
  enabling, 64
  in Node Prism, 190
  saving, 64
  triggering conditions for, 58
Events menu, 63
executing a program, 49
execution pointer, 25, 228
  in Node Prism, 189
execution status, finding out in Node Prism, 189
expressions, writing in Prism, 31

F

F1 key, 14, 131
F10 key, 14, 17, 18
f77, 8
fg command, 189
file command, 54
File menu in visualizers, using, 89
File selection, 22, 53, 66
focus, 13
fonts, changing the default, 150
Fortran intrinsic functions, 33
front end, 9
func command, 54
Func selection, 22, 23, 54, 66
function definition, displaying in the source window, 23
functions, choosing the correct, 31

G

-g compiler option, 8, 66
gcc, extensions to C not supported, 8
Global Prism, 157
  entering Node Prism from, 160
global/local programs
  using Prism with, 185
  visualizing data in, 207
Glossary selection, 133
graph visualizers, 92
  field height of, 95

Version 2.0, April 1994
Copyright © 1991–1994 Thinking Machines Corporation

minimum and maximum of, 95
gwm, 10

H

help, getting, 131
help command, 133
help system
overview of, 5
using, 132
hide command, 223
history region, 26, 228
using, 27
HOST_PAUSE_POINT environment variable, 183

I

I-beam, 228
I/O, 51
specifying the Xterm for, 145, 154
icons, 19
immediate action, 228
Index selection, 132
infinities, detecting, 36
interrupt command, 187
Interrupt selection, 26, 52
ending a wait in Node Prism, 188
in Node Prism, 188
interrupted PN set, 166, 171, 187
interrupting execution, 52
isactive intrinsic, 169, 170

K

keyboard, using in the menu bar, 17
keyboard accelerators, 18, 229
keyboard alternatives to the mouse, 13

L

languages supported in Prism, 8
leaving Prism, 39
libprism2.a, 9
line-number region, 3, 229
in Node Prism, 194
using, 24
list command, 217, 224
lists, using, 21
load command, 43
can't be used in actions field, 61
Load Data selection, 125, 217
Load selection, 42
loading a program, 41
location cursor, 13, 229
log command, 29, 155
logging commands and output, 29

M

mail, sending, 136
mailing list, 137
main, 74
make command, 130
Make selection, 128
make utility, 128, 145
makefile
creating, 128
using, 128
Man Pages selection, 135
manual pages
viewing, 135
viewing in commands-only Prism, 218
Mark Stale Data, 145
master pane, in split source window, 224
MAXLOC intrinsic function, 86
MAXVAL intrinsic function, 33
memory, examining the contents of, 75
menu bar, 3, 229
using, 16
message-passing programs
structure of, 182
use of Node Prism with, 157
Meta key, 14, 18
MIMD programs, 157
MINVAL intrinsic function, 33
MIT X11R4, 9
mnemonics, 17, 229
Motif keyboard translations, changing, 153
mouse
getting help on using, 133

Copyright © 1991–1994 Thinking Machines Corporation

using, 13
using in the menu bar, 16
mouse pointer, 13, 229
mwm, 10

N

names, resolving, 31
NaNs, detecting, 36
NCD X11R4, 9
next command, 51
in Node Prism, 187
Next selection, 51
nexti command, 52
Node Prism, 2
commands-only version, 189
customizing, 214
debugging in, 190
entering, 159
events in, 190
executing a program in, 181
overview of, 157
performance analysis in, 210
prompt in, 176
shortening, 177
scope in, 199
visualizing data in, 207
nodes
interrupting, 187
waiting for, 187

O

olwm, 10
on-line documentation
obtaining, 134
obtaining in commands-only Prism, 218
Online Doc selection, 134
Options menu in visualizers, using, 89
output
logging, 29
redirecting, 28
in **-CX** version of Prism, 219
Overview selection, 133

P

Paris programs
compiling for Prism, 9
defining types for, 30
partition manager, 9
pathmap command, 155, 162
paths, mapping in remote execution, 162
pcoord, 34
perf command, 121, 217
redirecting output to X window, 219
perfadvice command, 123, 217
perfload command, 125, 217
performance advisor, 122, 229
performance analysis, in Node Prism, 210
performance data
collecting, 112
outside of Prism, 113
displaying, 113
displaying in the command window, 121
for C* and CM Fortran programs run on a Sun-4, 110
interpreting, 122
overhead of collecting, 111
what is collected, 109
performance data files, saving and loading, 124
Performance Data window, 115
in Node Prism, 210
Resources pane, 116
Source-Lines pane, 121
perfsave command, 125, 217
pn command, 178, 200
cannot be used in event actions, 193
PN Debug selection, 78, 158, 160
PN sets, 157
cycling through the members of, 179
defining, 166
syntax for, 166
deleting, 174
dynamic, 166
and events, 191
and the current PN set, 176
contrasted with variable PN sets, 171

Version 2.0, April 1994
Copyright © 1991–1994 Thinking Machines Corporation

naming, 169
predefined, 166
using, 163
using in commands, 180
variable, 169
and events, 192
and the current PN set, 177
contrasted with dynamic PN sets, 171
evaluating membership in, 170
viewing the contents of, 172
PN Sets selection, 164
PN Sets window, 172
changing the current PN set via, 175
cycling via, 179
using, 164
zooming in, 172
PN-set qualifier, 180
cannot be used in event actions, 193
lists of commands that accept, 181
pndbx, 78
running on a CM-5, 78
pnset command, 175, 176, 177, 200
cannot be used in event actions, 193
pnset keyword, 167
pnstatus command, 189
print command, 85
redirecting output to X window, 219
Print dialog box, 82
Print selection (**Debug** menu), 82
in Node Prism, 207
Print selection (**Events** menu), 83
printenv command, 38
printing
difference from displaying, 80
from the command window, 85
from the **Debug** menu, 82
from the event table, 84
from the **Events** menu, 83
from the source window, 22, 83
Prism
commands-only
and Prism resources, 148
issuing commands in, 216
leaving, 218
specifying, 11, 215
useful commands in, 217
using with CMAX, 226
entering, 10
initializing, 155
languages supported in, 8
leaving, 39
look and feel of, 2
mailing list for, 137
overview of, 1
sending mail about, 136
versions of, 2
prism command, 10
-C option, 11, 215
-connect option, 11, 160
-CX option, 11, 219
-node option, 11, 159
Prism defaults, changing, 147
Prism resources, 229
table of, 147
and commands-only Prism, 148
Prism.cppPath, 214
Prism.dialogColor, 151
Prism.editGeometry, 149
Prism.editor, 149
Prism.errorBell, 154
Prism.errorwin, 149
Prism.helpColor, 151
Prism.mainColor, 151
Prism.markStaleData, 154
Prism.pathMap, 155
Prism.spectralMapSize, 150
Prism.textBgColor, 151
Prism.textFont, 150
Prism.textManyFieldTranslations, 152
Prism.textMasterColor, 151
Prism.textOneFieldTranslations, 152
Prism.useXterm, 154
Prism.vizcolormap, 150
prism-talk@think.com, 137
Prism*fontList, 150
Prism*XmText.fontList, 150
.prism_defaults, 146
prism_define_name function, 104
prism_mimd_server, 161

Copyright © 1991–1994 Thinking Machines Corporation

.prisminit file, 12, 30, 31, 155
  and Node Prism, 214
procedures, displaying performance data on, 119
process, running
  attaching to and detaching from, 44
  loading, 10
PRODUCT intrinsic function, 33
programs
  executing, 49
  loading into Prism, 41
  reloading into Prism, 44
  rerunning, 50
ps command, 11, 45
pushbutton command, 141, 155, 216
pwd command, 38

Q

qualified names, 31, 229
  using, 32
quit command, 39, 218
  in Node Prism, 185
Quit selection, 39

R

radix, changing, 108
RANK intrinsic function, 33
rankof, 34
REAL intrinsic function, 33
registers, examining the contents of, 75, 85
release notes
  viewing, 136
  viewing in commands-only Prism, 218
Release Notes selection (**Doc** menu), 136, 144
Release Notes selection (**Help** menu), 133
reload command, 44
remote execution, 11, 160
  mapping paths in, 162
  specifying mappings between paths for, 154
rerun command, 50
resize box, 26, 230
resolving names, 31, 230
resources, 230
  displaying data on, 116
return command, 51
  can't be used in actions field, 61
Return key, 14
Run (args) selection, 50
run command, 50
  and Node Prism, 183
  can't be used in actions field, 61
Run selection, 50
running PN set, 166

S

safety, turned off when collecting performance data, 112
Save Data selection, 124
scope, in Node Prism, 199
scope pointer, 25, 230
scroll bar, 20
select command, 225
set command, 142
  $d_precision and **$f_precision** variables, 95
  $dp variable, 81
  $page_size variable, 217
  $prompt_length variable, 177
setenv command, 38
sh command, 37
shapeof, 34
Shell selection, 37
show command, 223
show events command, 64, 65, 71, 73, 193, 217
show pnset command, 173, 176, 177
show pnsets command, 164, 170, 173
  redirecting output to X window, 219
Silicon Graphics X11R4, 9
snapshot window, 28, 84
source code
  editing, 127
  moving through, 22
source command, 29, 64
source files, creating a directory list for, 55

Version 2.0, April 1994
Copyright © 1991–1994 Thinking Machines Corporation

source lines
displaying corresponding in split source window, 225
displaying performance data on, 121
source window, 3, 230
scrolling, 22
splitting, 23
splitting for CMAX program, 222
using, 21
SPARC registers, 77
status messages, 52
status region, 3
step command, 51
can't be used in actions field, 61
in Node Prism, 187
Step selection, 51
stepi command, 52
stepout command, 51
Stepout selection, 51
stepping through a program, 51
Stop <cond> button, 68
Stop <loc> selection, 67
Stop <var> selection, 68
stop command, 68
stopi command, 69, 71
stopped keyword, 61
stopped PN set, 166, 169, 171
structures, visualizing, 99
in commands-only Prism, 219
subsystems, 230
SUM intrinsic function, 33
surface visualizers, 92
field height of, 95
minimum and maximum of, 95

T

Tab, 14
Tear-off dialog box, 140
tear-off region, 3, 230
resizing, 140
using, 139
Tear-off selection, 140
tearoff command, 140, 155, 216
text, selecting in source window, 22
text font, 145
text visualizers, 4, 90
precision of, 95
text widgets, changing keyboard translations in, 152
threshold visualizers, 4, 91
threshold of, 96
timers, 124
and performance analysis, 111
Trace <cond> button, 72
Trace <loc> selection, 72
Trace <var> selection, 72
trace command, 69, 73
Trace selection, 72
tracei command, 69, 73
traces
deleting, 72, 73
in Node Prism, 190
synchronization required for, 192
tracing program execution, 71
triggering conditions for events, 58, 230
Tutorial selection, 8, 133
tvtwm, 9
twm, 9
type command, 30

U

unalias command, 142
union members, visualizing in structure visualizers, 103
UNIX commands, issuing, 37
unset command, 142
unsetenv command, 38
untearoff command, 140, 216
up command, 75
Up selection, 75
use command, 56
Use selection, 44, 55
Using Help selection, 133
/usr/lib/X11/rgb.txt, 145, 150
uwm, 10

Copyright © 1991–1994 Thinking Machines Corporation

V

variables
  changing the values of, 107
  choosing the correct, 31
  printing the type of, 106
  setting up alternative names for, 141
vector units, 204
vector visualizers, 93
  minimum and maximum of, 95
vector-unit memory
  errors files for, 204
  printing, 81
vector-unit registers
  errors file for, 204
  examining the contents of in Node Prism, 200
visualization parameters, 94
visualizer color file
  creating, 145
  sample, 146
visualizers, 4, 86, 230
  closing, 99
  displaying a ruler for, 96
  displaying from the source window, 22
  field width of, 95
  in Node Prism, 207
  setting the context for, 97
  statistics for, 97
  structure, 99
  treatment of stale data in, 145
  types of, 90
  updating, 99
  working with, 86

W

Wait Any selection, 188
`wait` command, 187
  `any` argument, 188
  `every` argument, 188
Wait Every selection, 188
watchpoint, 58, 231
`whatis` command, 106
  in Node Prism, 207
Whatis selection, 106
`when` command, 68
`where` command, 74
  in Node Prism, 199
  Node Prism version, redirecting output to X window, 219
Where graph, 194
  and the current PN, 178
  moving through, 198
  panning and zooming in, 196
  shrinking portions of, 198
  visualizing in commands-only Prism, 219
Where selection, 74
  in Node Prism, 194
Where window, 74, 75
`whereis` command, 32
`which` command, 32
window managers, 19
  supported, 9
windows
  deleting and destroying, 19
  using, 19
WorldView, 132

X

X resource database, adding Prism resources to, 148
X servers, supported, 9
X toolkit command-line options, 12
X Window System, 1
`xman`, 135
`xrdb`, 148
Xterm, specifying for I/O, 154

Version 2.0, April 1994
Copyright © 1991–1994 Thinking Machines Corporation