# A TITANic Catalog of Features & Surface Types Revealed by Cassini SAR

and Its Application to Studying Saturn's Largest Moon

Christopher Tsai (tsaic@stanford.edu)

Lauren Catherine Wye (lcwye@stanford.edu)

Professor Howard Zebker (zebker@stanford.edu)

June 28, 2006 - September 1, 2006



#### Introduction to Titan and Cassini Radar

Titan, Saturn's largest moon with a radius of 2575 km, is difficult to visualize by normal infrared and spectroscopic methods because of its thick, absorbing atmosphere. Thus, the Cassini-Huygens mission uses the microwave RADAR instrument (2.17-cm wavelength) to minimize atmospheric effects. The Huygens probe entered Titan's atmosphere and landed on the surface in January 2005. The Cassini orbiter, halfway through its four-year mission, supplies us with two key measurements: 1) coarseresolution scatterometer data across a wide range of incidence angles, which will attain near-global coverage, and 2) high-resolution Synthetic Aperture Radar (SAR) images acquired at a fixed incidence angle, to cover about 30% of Titan's surface (Elachi et al., 2005b). Cassini has thus far returned SAR images of the regions outlined below, labeled by orbit number, with TA occurring first. We view and study the swaths with our program disfloat to see images like Figure B. These radar reflectivity (normalized radar cross-section, or oo images, as well as their latitude and longitude, are stored in Basic Image Data Record (BIDR) files. The radar reflectivity imaged in Figure B varies with surface slope, roughness, and composition. Brighter regions signify higher reflectivity  $\sigma_0$ .




Figure A (Left): Highresolution SAR coverage of Titan, currently panning ≈10% of urface. By 2008, SAR lata will cover ≈30% of NOTE: The infrared maging device used to enerate the background annot view the north olar region, so the area

mains uncharted (black).




# Objective: Compiling a Catalog of Features & Surfaces

The Cassini Team has analyzed data from both the SAR and scatterometer modes, each with its own advantage. The SAR's high-resolution images have allowed scientists to identify specific types of features, such as dunes, craters, lakes, and flows, and their location on the surface; meanwhile, scatterometer data, with its wide range of incidence angles, reveals the Reflectivity-vs.-Angle relationship, which can be fit with backscatter curves to calculate surface properties.

My research has focused on classifying features and radar reflectivity seen in SAR images. While the Cassini Radar Team has already identified features, I have been devising ways to categorize them systematically in a database of text files. By grouping features of similar types and listing their latitude, longitude, and average normalized radar cross-section in text files, the catalog can distinguish precise locations of features and surface terrains, providing a systematic way of studying them in unison and modeling their trends in the scatterometer data, where specific locations are not readily apparent.

# Methodology and Measurement Procedure



values, which we box-average in 4x4 sets to compress files.

#### Download and compress noise-subtracted SAR image files to a viewable size.

BIDR files consume hundreds of megabytes; the file is over-magnified, so we compress the image stored in the  $\sigma_0$  BIDR file by replacing 4x4 sections of pixels with their average value to see more of the surface at once without losing too much feature detail.

#### Discern and catalog detailed features resembling one of several identified types.

Dune fields are most prevalent across imaged regions, but craters, lakes, flows, and vestiges of features also appear. In separate files, we also catalogued unidentified features, such as lines, rings, dots, and peculiar markings. We tagged each feature with its type and the (x,y) coordinates of its bounding polygon's vertices (as shown in Figure D), entering groups into their respective

## Smoothen the compressed image with an averaging filter.

Low-pass filtering blurs the image and allows us to distinguish large regions with similar normalized radar cross-section or reflectivity  $(\sigma_0)$ .

4. Discern and catalog surface regions that share a similar  $\sigma_0$  value. Regions sharing a backscatter coefficient could comprise similar material (observing at similar incidence angles removes the angular dependence of  $\sigma_0$ ), so we catalog them together.

Figure D: The database describes each feature by the vertices of its

#### Extract the latitude and longitude of features and regions based on their (x,y) coordinates.

Latitude and longitude values have their own BIDR files, corresponding pixel-for-pixel with the image file. We automate the extraction procedure to produce text file lists and MatLab data vectors for plotting.

#### 7. Systematically compute the average $\sigma_0$ value for each region.

A program operating similarly to MatLab's inpolygon averages  $\sigma_0$  values within a specified boundary.

#### 8. Determine logical bin cutoff values to separate regions of different types in text files.

Each range of values denotes a different surface type, and categorization expedites access to each type.

## Normalized Radar Cross-Section (Backscatter Coefficient)

The normalized radar cross-section, also known as the backscatter coefficient, or reflectivity, measures the reflective strength of a distributed radar target. It is the radar cross-section per unit area on the surface ground. We can compute values obtained by Cassini Radar by solving the Radar Equation for  $\sigma_0$ :




 $P_r = power transmitted by radar$ G = antenna gain in direction of surface R = distance from source to surface

 $dP_{r}$  = instantaneous power in one pulse

dS = differential surface area element

## Classification of Titan's Features



Features assume many different shapes and sizes; anything that differs from its surroundings could be a feature. Dunes are the most common feature in the regions mapped thus far, but lakes recently debuted in T16. Some features have not been officially identified; for example, the discolored rings could be eroded craters but cannot yet be catalogued as such. Collectively, the features exhibit possible cryovolcanism, impact cratering, fluvial processes, aeolian activity, and possible methane cycle activity

Belet.(T3)



Features Circles Craters Dunes Flows Hills Lakes Lines Marks Mountains Peculiarities Rings






Figure J: Dune patches with lower  $\sigma_0$  than surroundings. Not extended like

Figure O: Locations of all currently catalogued dune fields, craters, and lakes on Titan's surface. Dunes generally lie in the equatorial region, while lakes seem to favor the poles. We continue to seek trends in the

# Classification of Titan's Surface Regions by Reflectivity









Figure Q: Vastly different reflective values exist in adjacent regions (T13). The white area, called Xanadu, is the largest, brightest region on Titan.



Different average  $\sigma_0$  values separate surface regions of different types. The reflectivity of a surface type is closely related to the surface material and slope. Brighter regions signify higher  $\sigma_0$  values.

The inpolygon-based averaging algorithm computes average  $\sigma_0$ for regions given peripheral vertices. We then choose bin ranges so we can group regions of a similar type.





Figure S: Potential application of the surface region  $\sigma_0$  catalog. After the catalogued areas across all swaths have been divided into bins, we can locate them on a latitude-longitude plot and look for trends in the distribution of regions in a certain  $\sigma_0$ range. Pictured are the darkest and brightest  $\sigma_0$  bins observed

# Application of the Catalog to Analysis

We can fit backscatter model curves to the Average σ<sub>0</sub>-vs.-Incidence Angle data from the scatterometer to determine the mean dielectric \} constant and surface slope of several large regions on Titan (Wye, 2006b).

The features catalog and surface reflectivity database could permit more precise analysis; by using  $\sigma_0$  values from smaller but strongly similar areas, we can determine properties like the dielectric constant and slope for dunes, craters, lakes, bright regions, dark regions, and other groups. We would know exactly where to find them in the scatterometer data since it follows the same latitude-longitude system as the observed SAR data.



Parameters in the model relate to the mean dielectric constant, RMS surface slope, roughness, etc. (Wye, 2006b).