Published: 05/27/68

<u>Identification</u>

Conversion of Multics user name to CTSS user name find_12_dir
J. H. Cecil

<u>Purpose</u>

Find_12_dir is used to convert a Multics user name consisting of a Multics person name and project name to the corresponding 6 character CTSS project name and 6 character CTSS person name.

Usage

call find_12_dir (multics_user_name, prob, prog);

where multics_user_name is the multics pathname to be converted, consisting of the Multics person name and project name in the form ">user_dir_dir>multics_person_name.multics_project_name", and prob and prog are the resulting 6 character CTSS project and person names returned.

Multics_user_name may be passed as any length character string varying or nonvarying but, if a legal Multics directory name, it will always be 17 to 53 characters. Prob and prog are returned as 6 character strings, padded with blanks on the left if the CTSS names are less than 6 characters long.

<u>Implementation</u>

The 3 parts of the multics_user_name ("user_dir_dir>", multics_person_name, and multics_project_name) are separated. The project_name and person_name portions to be converted are looked up in the EPLBSA segment, user_name_table\$project and user_name_table\$person, respectively. The corresponding CTSS names found are then padded on the left with blanks and returned in prob and prog. If no entry is found in user_name_table for the multics project or person name, the CTSS project or person name returned is set to 6 blanks, an error message given, and find_12_dir continues with a normal return. Thus the calling program must check for blank arguments returned if one wishes to find out if the conversion was completely successful.

In converting the person_name, the general rule is to use, for the CTSS person name, the CTSS programmer number associated with the Multics person name. Suggested project name correspondences are:

CTSS	Multics
T0234	mac
T0269	btl
T0288	ge

The conversion table for the project and person names is described in the writeup on user_name_table.

Example:

call find_12_dir(">user_dir_dir>cecil.mac", prob, prog); would return "TO234" in prob and "6044" in prog.