MULTICS SYSTEM-PROGRAMMERS " MANUAL SECTION BL. 1. 03A PAGE 1

Published: 05/03/68

Identification

Addendum to BL.1.03 J. M. Grochow, N. I. Morris

New control words: bind. bind-names

With the integration of segment binding and system tape generation two new control lines have been added to the MST header file:

bind: yes;

must appear if this is a header for a segment to be bound in this run ("no" if this is a bound segment but is already bound).

bind_names: $\alpha, \beta, \gamma, \delta, \ldots, \omega$;

where α , β , γ , . . . are the names of the component segments. This statement must appear after the "bind:" statement.

Neither of these control lines need be present in a header for a non-bound segment.

Obsoleted control word: loadname

The new way of specifying a segment loadname is to place it in parentheses following the segment name:

α (β); name:

Where β previously would have appeared in a "loadname" statement.

Loadnames may also be specified for components of a bound segment:

bind_names: $\alpha(a^{\prime}), \beta(\beta^{\prime}), \gamma(\gamma^{\prime});$

The control word "loadname" will no longer be recognized.

In cases where it is desired to call a segment off the library, bind it, and then write it on an MST with a different name, the following may be used:

name:

 α $\{\beta\}$;

where α will be the MST name and β is the library name.

MULTICS SYSTEM-PROGRAMMERS * MANUAL

In summary:

name on library	in 6.36 during binder and MSTG_run	on MST	control line
α	α	α	name: α ;
α	β	α	name: $\alpha(\beta);$
β	β	α	name: $\alpha \{\beta\}$:

Neither of the loadname options is allowed on a "name" statement referring to a bound segment.

(It will be remembered that " $\{$ " is " ϕ (" on a 2741 or 1050.).