Function Index

This index lists functions, symbols, and related terms that are described in this document. References with boldface page numbers are defining references.

A

addr, port object slot, **280**
allocated, port object slot, **280**

B

byte_counter, port object slot, **280**

C

CMAML_allocate_rport, function, **287**
CMAML_allocate_this_rport, function, **287**
CMAML_cp_long_am_nwords, function, **266**
CMAML_disable_interrupts, function, **302**
CMAML_enable_interrupts, function, **302**
CMAML_free_rport, function, **287**
CMAML_get_rport_*slot*, function, **289**
CMAML_inside_interrupt_handler, function, **302**
CMAML_interrupt_status, function, **302**
CMAML_n_to_pop, function, **264**
CMAML_number_of_free_rports, function, **287**
CMAML_number_of_rports, function, **287**
CMAML_pcopy, function, **282**
CMAML_pn_long_am_nwords, function, **266**
CMAML_poll, function, **300**
CMAML_poll_wait, function, **300**
CMAML_poll_while_lt, function, **300**
CMAML_pop, function, **251**
CMAML_popd, function, **251**
CMAML_popn, function, **257**
CMAML_popnd, function, **257**
CMAML_poptofirst, function, **254**
CMAML_poptofirst_ra, function, **254**
CMAML_poptofirst_rla, function, **254**
CMAML_poptofirstd, function, **254**
CMAML_poptofirstd_ra_d, function, **254**
CMAML_poptofirstd_rla_d, function, 254
CMAML_reply, function, **229**
CMAML_reply_arrpop0, function, **243**
CMAML_reply_arrpop0_tohost, function, **243**
CMAML_reply_arrpop1, function, **243**
CMAML_reply_arrpop1_tohost, function, **243**
CMAML_reply_arrpop2, function, **243**
CMAML_reply_arrpop2_tohost, function, **243**
CMAML_reply_poll, function, **300**
CMAML_reply_tohost, function, **229**
CMAML_reply_va, function, **233**

Copyright © 1995 Thinking Machines Corporation

CMAML_reply_va_tohost, function, **233**
CMAML_reply_vapop, function, **238**
CMAML_reply_vapop_tohost, function, **238**
CMAML_request, function, **229**
CMAML_request_arrpop0, function, **243**
CMAML_request_arrpop0_tohost, function, **243**
CMAML_request_arrpop1, function, **243**
CMAML_request_arrpop1_tohost, function, **243**
CMAML_request_arrpop2, function, **243**
CMAML_request_arrpop2_tohost, function, **243**
CMAML_request_poll, function, **300**
CMAML_request_tohost, function, **229**
CMAML_request_va, function, **233**
CMAML_request_va_tohost, function, **233**
CMAML_request_vapop, function, **238**
CMAML_request_vapop_tohost, function, **238**
CMAML_restore_ctrlregs, function, **304**
CMAML_restore_dataregs, function, **304**
CMAML_restore_fpuregs, function, **304**
CMAML_rpc, function, **229**
CMAML_rpc_arrpop0, function, **243**
CMAML_rpc_arrpop0_tohost, function, **243**
CMAML_rpc_arrpop1, function, **243**
CMAML_rpc_arrpop1_tohost, function, **243**
CMAML_rpc_arrpop2, function, **243**
CMAML_rpc_arrpop2_tohost, function, **243**
CMAML_rpc_tohost, function, **229**
CMAML_rpc_va, function, **233**
CMAML_rpc_va_tohost, function, **233**
CMAML_rpc_vapop, function, **238**
CMAML_rpc_vapop_tohost, function, **238**
CMAML_save_ctrlregs, function, **304**
CMAML_save_dataregs, function, **304**
CMAML_save_fpuregs, function, **304**
CMAML_scopy, function, **282**
CMAML_set_rport_*slot*, function, **289**
CMAML_wait, function, **300**
CMMD_all_channels_free, function, **132**
CMMD_all_channels_free_wait, function, **132**
CMMD_all_msgs_done, function, **93**, **104**
CMMD_all_msgs_wait, function, **94**, **106**
CMMD_all_receives_done, function, **93**, **105**
CMMD_all_sends_done, function, **93**, **105**
CMMD_available_receives, function, **71**
CMMD_available_sends, function, **71**
CMMD_bc_from_host, function, **404**, **412**
CMMD_bc_from_host_v, function, **414**
CMMD_bc_to_nodes, function, **142**
CMMD_bytes_received, function, **69**
CMMD_bytes_sent, function, **69**
CMMD_close_receive_channel, function, **130**
CMMD_close_send_channel, function, **130**
CMMD_concat_elements_to_host, function, **404**, **418**
CMMD_concat_with_nodes, function, **186**
CMMD_disable_interrupts, function, **207**
CMMD_disable_safety, function, **397**
CMMD_distrib_to_nodes, function, **404**, **416**
CMMD_enable, function, **409**
CMMD_enable_host, function, **409**
CMMD_enable_interrupts, function, **207**
CMMD_enable_safety, function, **397**
CMMD_error, function, **377**
CMMD_error_string, function, **376**
CMMD_fget_io_mode, function, **341**
CMMD_free_mcb, function, **95**
CMMD_fset_io_mode, function, **339**

Version 3.3, April 1995
Copyright © 1995 Thinking Machines Corporation

CMMD_gather_from_nodes, function, **404**, **418**
CMMD_get_errno, function, **374**
CMMD_get_global_or, function, **197**
CMMD_get_io_mode, function, **341**
CMMD_get_open_mode, function, **332**
CMMD_get_rearrange_size, function, **344**
CMMD_global_creat, function, **336**
CMMD_global_fopen, function, **337**
CMMD_global_open, function, **334**
CMMD_global_socket, function, **357**
CMMD_global_suspend_servers, function, **426**
CMMD_host_node, function, **410**
CMMD_independent, constant, **333**
CMMD_inside_interrupt_handler, function, **209**
CMMD_interrupt_status, function, **209**
CMMD_is_channel_readable, function, **124**
CMMD_is_channel_writable, function, **124**
CMMD_local, constant, **332**
CMMD_max_rearrange_size, function, **346**
CMMD_mcb_buffer, function, **101**
CMMD_mcb_bytes, function, **101**
CMMD_mcb_dest, function, **99**
CMMD_mcb_node, function, **99**
CMMD_mcb_pending, function, **97**
CMMD_mcb_source, function, **99**
CMMD_mcb_tag, function, **101**
CMMD_msg_done, function, **93**, **102**
CMMD_msg_pending, function, **68**
CMMD_msg_sender, function, **70**
CMMD_msg_tag, function, **70**
CMMD_msg_wait, function, **94**, **106**
CMMD_node_timer_busy, function, **384**
CMMD_node_timer_clear, function, **381**
CMMD_node_timer_elapsed, function, **384**
CMMD_node_timer_idle, function, **384**
CMMD_node_timer_start, function, **382**
CMMD_node_timer_stop, function, **383**
CMMD_open_receive_channel, function, **118**
CMMD_open_send_channel, function, **118**
CMMD_partition_size, function, **67**
CMMD_physical_blocking_factor, function, **369**
CMMD_physical_read, function, **371**
CMMD_physical_write, function, **370**
CMMD_poll, function, **211**
CMMD_poll_for_services, function, **426**
CMMD_PR_C_receive, channel state constant, **122**
CMMD_PR_C_send, channel state constant, **122**
CMMD_PR_Close_error, channel state constant, **122**
CMMD_PR_Free, channel state constant, **122**
CMMD_PR_O_receive, channel state constant, **122**
CMMD_PR_O_send, channel state constant, **121**
CMMD_PR_Readable, channel state constant, **122**
CMMD_PR_Sendable, channel state constant, **121**
CMMD_PR_Sent, channel state constant, **121**
CMMD_PR_Unreadable, channel state constant, **122**
CMMD_receive_async, function, **85**
CMMD_receive_bc_from_host, function, **404**, **412**
CMMD_receive_bc_from_host_v, function, **414**
CMMD_receive_bc_from_node, function, **142**
CMMD_receive_block, function, **51**
CMMD_receive_block_v, function, **51**
CMMD_receive_channel_status, function, **121**
CMMD_receive_element_from_host, function, **404**, **416**

Copyright © 1995 Thinking Machines Corporation

CMMD_reduce_*type*, function, **145**
CMMD_reduce_*type*_finish, function, **153**
CMMD_reduce_*type*_start, function, **148**
CMMD_reduce_done, function, **151**
CMMD_reduce_from_nodes_*type*, function, 420
CMMD_reduce_from_nodes_v, function, **423**
CMMD_reduce_to_host_*type*, function, 420
CMMD_reduce_to_host_v, function, **423**
CMMD_reduce_v, function, **156**
CMMD_reset_partition_size, function, **394**
CMMD_reset_receive_channel, function, **128**
CMMD_scan_*type*, function, **160**
CMMD_scan_*type*_finish, function, **175**
CMMD_scan_*type*_start, function, **167**
CMMD_scan_done, function, **174**
CMMD_scan_v, function, **181**
CMMD_self_address, function, **65**
CMMD_send_and_receive, function, **54**
CMMD_send_and_receive_v, function, **54**
CMMD_send_async, function, **81**
CMMD_send_block, function, **47**
CMMD_send_block_v, function, **47**
CMMD_send_channel_status, function, **121**
CMMD_send_noblock, function, **88**
CMMD_service_loop, function, **426**
CMMD_set_global_or, function, **197**
CMMD_set_io_mode, function, **339**
CMMD_set_msg_matching_fcn, function, **392**
CMMD_set_open_mode, function, **332**
CMMD_set_rearrange_size, function, **342**
CMMD_swap, function, **58**
CMMD_swap_v, function, **58**
CMMD_sync_bc, constant, **333**
CMMD_sync_host_with_nodes, function, **411**
CMMD_sync_seq, constant, **333**
CMMD_sync_with_host, function, **411**
CMMD_sync_with_nodes, function, **194**, **195**
CMMD_write_channel, function, **126**

D

dftruncate, function, **353**
dlength, function, **349**
dseek, function, **350**
dtell, function, **352**

E

ECMMDBADMODE, I/O error type, **323**
ECMMDINCONSISTENT, I/O error type, **323**
ECMMDNOMATCH, I/O error type, **323**

H

handler, port object slot, **280**
handler_arg2, port object slot, **280**

T

total_nbytes, port object slot, **280**

Copyright © 1995 Thinking Machines Corporation