Index

A

access restrictions, 16
accounting information, obtaining, 41

B

batch. *See* NQS
batch queues 2
  creating a default, 35
  creating, starting, and enabling, 21–42
  overview of configuring, 20–42
  specifying, 6
  stopping, disabling, and deleting, 25–42
  who can use, 26–42
batch requests
  deleting, 12
  obtaining information about, 13
  output from, 7
  receiving mail about, 11
  setting limits on, 27–42
  setting priority for, 11
  states of, 13
  submitting, 4

C

corefile, placed in home directory, 9
CPU time, setting limit on, 9

D

debugging NQS errors, 37

E

/etc/hosts.equiv, 40
error messages, NQS, 37

H

hostnames, 5

I

installing NQS, 18
interqueue priority, 21, 32, 36
intraqueue priority, 11
  setting the default, 36–42

L

limits, setting for batch requests, 27
log files, 37
logging, NQS error output, 37
logging system, 37

M

machine ID, 38
mapping, between NQS computers, 37

N

nice values, 13
nmapmgr, 31
  running, 37–42
NQS
  configuring, 18–42
  installing, 18
  logging error information, 37
  logging error output from, 37
  managing, 18, 19, 34–42
  obtaining information about, 40
  overview of, 2
  shutting down, 34
  starting up, 18

NQS manager, 19
NQS operator, 19
nqsdaemon, 18, 35

P

pipe queues, 2, 17
  creating, configuring, and managing, 31–42
  order of submissions, 32
  overview of, 30–42
  server of, 32
  stopping, disabling, and deleting, 25–42
  who can use, 26–42
priority, setting for batch queues, 32

Q

qdel, 12
qlimit, 9
qmgr, 18–42
  abort queue command, 26
  add groups command, 26, 33
  add managers command, 20
  add queues command, 29
  add users command, 26, 33
  create batch_queue command, 21–42
  create complex command, 29
  create pipe_queue command, 32–42
  delete complex command, 29
  delete groups command, 27
  delete managers command, 20
  delete queue command, 25
  delete restriction_window command, 24–42
  delete users command, 27
  disable queue command, 25, 26
  enable queue command, 22–42
  help command, 40
  purge queue command, 25
  remove queue command, 29
  set complex run_limit command, 29
  set corefile_limit command, 27
  set data_limit command, 28
  set debug command, 37
  set default batch_request priority command, 36
  set default batch_request queue command, 35
  set log_file command, 37
  set managers command, 19
  set nice_value_limit command, 28
  set no_access command, 26
  set no_default batch_request queue command, 35
  set per_process cpu_limit command, 27
  set per_process permfile_limit command, 28
  set restriction_window command, 23, 25, 34
  set shell_strategy command, 35
  set stack_limit command, 28
  set unrestricted_access command, 27, 33
  set working_set_limit command, 28
  show command, 40
  start queue command, 23–42
  stop queue command, 25
  who can issue commands, 19–42
qstat, 12, 40
  –a option, 13
  –f option, 15
  –p option, 15
  –u option, 13
qsub, 3
  –e option, 8
  –lt option, 9
  –mb option, 11
  –me option, 11
  –mu option, 11
  –o option, 8
  –p option, 11
  –q option, 6
  –r option, 8
qsub, (cont.)
  –s option, 11

- options for, 4
- options in script file, 6

QSUB_QUEUE, 6
queue complexes, 16, 28
queues
- obtaining information about, 14
- status of, 14

R

request–ids, 5
restriction window, 16
- deleting, 24
- setting, 23

run limit, 15, 22, 33

S

script files, 5
- specifying a request from, 7

sequence numbers, 5
shell, choosing, 10
shell strategy, 10, 35–42
shownqs script, 40
shutting down NQS, 34
SIGKILL, 26, 34
signals, sending to a batch request, 12
SIGTERM, 24, 26, 34
standard input, specifying a request from, 7
startnqs script, 18
stopnqs script, 34
superuser, 19
- access to queues, 26

T

tty, message about, 9

U

/usr/adm/nqs, 41
/usr/bin, NQS commands in, 18
/usr/etc, NQS daemons in, 18
/usr/spool/nqs/log.daemon, 18