


Estimated measurement uncertainties of natural convection at $\theta = 0.0$.


Symbol	Nominal	Sensitivity	Bias	Uncertainty	Component
ΔT	10.5K	+22.0%/K	0.10K	2.20%	LM35C differential
P	101kPa	+0.0007%/Pa	1.5kPa	1.02%	MPXH6115A6U air pressure
C_{pt}	4.24kJ/K	+0.046%/(J/K)	42J/K	1.96%	plate thermal capacity
C_V	1.000	−13.2%	0.100	1.32%	vertical reuptake
L_c	0.305m	+594%/m	500um	0.30%	characteristic length
D_{PIR}	25.4mm	−514%/m	1.0mm	0.51%	insulation thickness
D_g	1.00mm	−521%/m	500um	0.26%	air gap
L_m	3.57mm	+1084%/m	500um	0.54%	side metal strip width
k_{PIR}	22.2 $\frac{mW}{K \cdot m}$	+0.497%/ $\frac{mW}{K \cdot m}$	1.1 $\frac{mW}{K \cdot m}$	0.55%	PIR thermal conductivity
ϵ_{XPS}	0.515	+35.4%	0.010	0.35%	XPS emissivity
ϵ_{tp}	0.890	+42.5%	0.015	0.64%	tape emissivity
Ω_{tp}	0.540	+28.9%	0.020	0.58%	tape coverage
ϵ_{rs}	0.040	+147%	0.010	1.47%	test-surface emissivity
ϵ_{wt}	0.900	+69.5%	0.025	1.74%	wind-tunnel emissivity
				4.32%	combined bias uncertainty

20180619T123939Z – mixed Convection – Roughness=1.04mm; T=18.1+10.5°C; +0.00°
34±4.4r/min, V=0.12m/s, Re=2473, Ra/L^3=1.037x10^9, h=3.54W/(K.m^2), U=0.330W/K, Nu=42.4



Estimated measurement uncertainties, bi-level 1mm roughness at $Re = 2473$.


Symbol	Nominal	Sensitivity	Bias	Uncertainty	Component
ΔT	10.5K	+21.6%/K	0.10K	2.16%	LM35C differential
P	99.8kPa	+0.0007%/Pa	1.5kPa	1.07%	MPXH6115A6U air pressure
C_{pt}	4.24kJ/K	+0.046%/(J/K)	42J/K	1.93%	plate thermal capacity
C_V	1.000	−12.8%	0.100	1.28%	vertical reuptake
L_c	0.305m	+579%/m	500um	0.29%	characteristic length
D_{PIR}	25.4mm	−498%/m	1.0mm	0.50%	insulation thickness
D_g	1.00mm	−505%/m	500um	0.25%	air gap
L_m	3.57mm	+1085%/m	500um	0.54%	side metal strip width
k_{PIR}	22.2 $\frac{mW}{K \cdot m}$	+0.485%/ $\frac{mW}{K \cdot m}$	1.1 $\frac{mW}{K \cdot m}$	0.54%	PIR thermal conductivity
ϵ_{XPS}	0.515	+34.5%	0.010	0.35%	XPS emissivity
ϵ_{tp}	0.890	+41.4%	0.015	0.62%	tape emissivity
Ω_{tp}	0.540	+28.1%	0.020	0.56%	tape coverage
ϵ_{rs}	0.040	+143%	0.010	1.43%	test-surface emissivity
ϵ_{wt}	0.900	+67.8%	0.025	1.69%	wind-tunnel emissivity
				4.24%	combined bias uncertainty
Symbol	Nominal	Sensitivity	Variability	Uncertainty	Component
ω	34.2r/min	+0.218%/(r/min)	4.4r/min	0.96%	fan rotation rate
				4.66%	RSS combined uncertainty



Estimated measurement uncertainties, bi-level 1mm roughness at $Re = 3011$.

Symbol	Nominal	Sensitivity	Bias	Uncertainty	Component
ΔT	10.3K	+21.7%/K	0.10K	2.17%	LM35C differential
P	100kPa	+0.0007%/Pa	1.5kPa	1.10%	MPXH6115A6U air pressure
C_{pt}	4.24kJ/K	+0.045%/(J/K)	42J/K	1.92%	plate thermal capacity
C_V	1.000	−12.5%	0.100	1.25%	vertical reuptake
L_c	0.305m	+571%/m	500um	0.29%	characteristic length
D_{PIR}	25.4mm	−481%/m	1.0mm	0.48%	insulation thickness
D_g	1.00mm	−488%/m	500um	0.24%	air gap
L_m	3.57mm	+1069%/m	500um	0.53%	side metal strip width
k_{PIR}	22.2 $\frac{mW}{K \cdot m}$	+0.469%/ $\frac{mW}{K \cdot m}$	1.1 $\frac{mW}{K \cdot m}$	0.52%	PIR thermal conductivity
ϵ_{XPS}	0.515	+33.6%	0.010	0.34%	XPS emissivity
ϵ_{tp}	0.890	+40.3%	0.015	0.60%	tape emissivity
Ω_{tp}	0.540	+27.4%	0.020	0.55%	tape coverage
ϵ_{rs}	0.040	+140%	0.010	1.40%	test-surface emissivity
ϵ_{wt}	0.900	+66.1%	0.025	1.65%	wind-tunnel emissivity
				4.20%	combined bias uncertainty
Symbol	Nominal	Sensitivity	Variability	Uncertainty	Component
ω	41.3r/min	+0.318%/(r/min)	3.4r/min	1.09%	fan rotation rate
				4.74%	RSS combined uncertainty


20180619T153646Z – mixed Convection – Roughness=1.04mm; T=18.4+10.2°C; +0.00°
58±3.1r/min, V=0.21m/s, Re=4215, Ra/L^3=1.009x10^9, h=3.96W/(K.m^2), U=0.369W/K, Nu=47.4



Estimated measurement uncertainties, bi-level 1mm roughness at $Re = 4215$.

Symbol	Nominal	Sensitivity	Bias	Uncertainty	Component
ΔT	10.2K	+21.2%/K	0.10K	2.12%	LM35C differential
P	99.9kPa	+0.0008%/Pa	1.5kPa	1.19%	MPXH6115A6U air pressure
C_{pt}	4.24kJ/K	+0.044%/(J/K)	42J/K	1.89%	plate thermal capacity
η	0.402	+60.5%	0.004	0.24%	anemometer calibration
C_V	1.000	−11.9%	0.100	1.19%	vertical reuptake
L_c	0.305m	+565%/m	500um	0.28%	characteristic length
D_{PIR}	25.4mm	−498%/m	1.0mm	0.50%	insulation thickness
D_g	1.00mm	−505%/m	500um	0.25%	air gap
L_m	3.57mm	+1048%/m	500um	0.52%	side metal strip width
k_{PIR}	22.2 $\frac{mW}{K \cdot m}$	+0.487%/ $\frac{mW}{K \cdot m}$	1.1 $\frac{mW}{K \cdot m}$	0.54%	PIR thermal conductivity
ϵ_{XPS}	0.515	+32.4%	0.010	0.32%	XPS emissivity
ϵ_{tp}	0.890	+38.8%	0.015	0.58%	tape emissivity
Ω_{tp}	0.540	+26.4%	0.020	0.53%	tape coverage
ϵ_{rs}	0.040	+134%	0.010	1.34%	test-surface emissivity
ϵ_{wt}	0.900	+63.3%	0.025	1.58%	wind-tunnel emissivity
				4.13%	combined bias uncertainty
Symbol	Nominal	Sensitivity	Variability	Uncertainty	Component
ω	58.4r/min	+0.416%/(r/min)	3.1r/min	1.31%	fan rotation rate
				4.89%	RSS combined uncertainty


20180620T034519Z – mixed Convection – Roughness=1.04mm; T=17.6+10.5°C; +0.00°
80±2.2r/min, V=0.29m/s, Re=5844, Ra/L^3=1.061x10^9, h=4.55W/(K.m^2), U=0.423W/K, Nu=54.5



Estimated measurement uncertainties, bi-level 1mm roughness at $Re = 5844$.

Symbol	Nominal	Sensitivity	Bias	Uncertainty	Component
ΔT	10.5K	+19.3%/K	0.10K	1.93%	LM35C differential
P	100kPa	+0.0009%/Pa	1.5kPa	1.34%	MPXH6115A6U air pressure
C_{pt}	4.24kJ/K	+0.042%/(J/K)	42J/K	1.80%	plate thermal capacity
η	0.402	+109%	0.004	0.44%	anemometer calibration
C_V	1.000	−10.7%	0.100	1.07%	vertical reuptake
L_c	0.305m	+561%/m	500um	0.28%	characteristic length
ς	2.00mm	−4452%/m	100um	0.45%	post height
D_{PIR}	25.4mm	−477%/m	1.0mm	0.48%	insulation thickness
D_g	1.00mm	−484%/m	500um	0.24%	air gap
L_m	3.57mm	+961%/m	500um	0.48%	side metal strip width
k_{PIR}	22.2 $\frac{mW}{K \cdot m}$	+0.467%/ $\frac{mW}{K \cdot m}$	1.1 $\frac{mW}{K \cdot m}$	0.52%	PIR thermal conductivity
ϵ_{XPS}	0.515	+28.7%	0.010	0.29%	XPS emissivity
ϵ_{tp}	0.890	+34.5%	0.015	0.52%	tape emissivity
Ω_{tp}	0.540	+23.4%	0.020	0.47%	tape coverage
ϵ_{rs}	0.040	+119%	0.010	1.19%	test-surface emissivity
ϵ_{wt}	0.900	+56.1%	0.025	1.40%	wind-tunnel emissivity
				3.90%	combined bias uncertainty
Symbol	Nominal	Sensitivity	Variability	Uncertainty	Component
ω	80.3r/min	+0.546%/(r/min)	2.2r/min	1.18%	fan rotation rate
				4.57%	RSS combined uncertainty


20180618T024836Z – mixed Convection – Roughness=1.04mm; T=17.6+10.2°C; +0.00°
113±2.4r/min, V=0.40m/s, Re=8261, Ra/L^3=1.037x10^9, h=5.54W/(K.m^2), U=0.515W/K, Nu=66.3



Estimated measurement uncertainties, bi-level 1mm roughness at $Re = 8261$.

Symbol	Nominal	Sensitivity	Bias	Uncertainty	Component
ΔT	10.2K	+18.1%/K	0.10K	1.81%	LM35C differential
P	101kPa	+0.0010%/Pa	1.5kPa	1.51%	MPXH6115A6U air pressure
C_{pt}	4.24kJ/K	+0.039%/(J/K)	42J/K	1.66%	plate thermal capacity
η	0.402	+172%	0.004	0.69%	anemometer calibration
C_V	1.000	−8.86%	0.100	0.89%	vertical reuptake
L_c	0.305m	+528%/m	500um	0.26%	characteristic length
L_T	8.34mm	+4361%/m	100um	0.44%	post length
ς	2.00mm	−10958%/m	100um	1.10%	post height
D_{PIR}	25.4mm	−419%/m	1.0mm	0.42%	insulation thickness
D_g	1.00mm	−425%/m	500um	0.21%	air gap
L_m	3.57mm	+833%/m	500um	0.42%	side metal strip width
k_{PIR}	22.2 $\frac{mW}{K \cdot m}$	+0.412%/ $\frac{mW}{K \cdot m}$	1.1 $\frac{mW}{K \cdot m}$	0.46%	PIR thermal conductivity
ϵ_{XPS}	0.515	+23.7%	0.010	0.24%	XPS emissivity
ϵ_{tp}	0.890	+28.5%	0.015	0.43%	tape emissivity
Ω_{tp}	0.540	+19.3%	0.020	0.39%	tape coverage
ϵ_{rs}	0.040	+98.7%	0.010	0.99%	test-surface emissivity
ϵ_{wt}	0.900	+46.2%	0.025	1.16%	wind-tunnel emissivity
				3.79%	combined bias uncertainty
Symbol	Nominal	Sensitivity	Variability	Uncertainty	Component
ω	113r/min	+0.611%/(r/min)	2.4r/min	1.45%	fan rotation rate
				4.77%	RSS combined uncertainty


20180618T002829Z – mixed Convection – Roughness=1.04mm; T=17.3+10.2°C; +0.00°
160±1.1r/min, V=0.57m/s, Re=11671, Ra/L^3=1.041x10^9, h=7.31W/(K.m^2), U=0.680W/K, Nu=87.7



Estimated measurement uncertainties, bi-level 1mm roughness at $Re = 11672$.

Symbol	Nominal	Sensitivity	Bias	Uncertainty	Component
ΔT	10.2K	+16.0%/K	0.10K	1.60%	LM35C differential
P	101kPa	+0.0010%/Pa	1.5kPa	1.53%	MPXH6115A6U air pressure
C_{pt}	4.24kJ/K	+0.036%/(J/K)	42J/K	1.51%	plate thermal capacity
η	0.402	+204%	0.004	0.82%	anemometer calibration
C_V	1.000	-6.81%	0.100	0.68%	vertical reuptake
L_c	0.305m	+425%/m	500um	0.21%	characteristic length
L_T	8.34mm	+6491%/m	100um	0.65%	post length
ς	2.00mm	-12215%/m	100um	1.22%	post height
D_{PIR}	25.4mm	-339%/m	1.0mm	0.34%	insulation thickness
L_m	3.57mm	+685%/m	500um	0.34%	side metal strip width
k_{PIR}	22.2 $\frac{mW}{K \cdot m}$	+0.334%/ $\frac{mW}{K \cdot m}$	1.1 $\frac{mW}{K \cdot m}$	0.37%	PIR thermal conductivity
ϵ_{tp}	0.890	+21.8%	0.015	0.33%	tape emissivity
Ω_{tp}	0.540	+14.8%	0.020	0.30%	tape coverage
ϵ_{rs}	0.040	+75.6%	0.010	0.76%	test-surface emissivity
ϵ_{wt}	0.900	+35.3%	0.025	0.88%	wind-tunnel emissivity
				3.51%	combined bias uncertainty
Symbol	Nominal	Sensitivity	Variability	Uncertainty	Component
ω	160r/min	+0.512%/(r/min)	1.1r/min	0.56%	fan rotation rate
				3.68%	RSS combined uncertainty


20180617T223249Z – mixed Convection – Roughness=1.04mm; T=16.7+10.9°C; +0.00°
226±1.8r/min, V=0.80m/s, Re=16450, Ra/L^3=1.120x10^9, h=9.09W/(K.m^2), U=0.846W/K, Nu=109.2



Estimated measurement uncertainties, bi-level 1mm roughness at $Re = 16448$.

Symbol	Nominal	Sensitivity	Bias	Uncertainty	Component
ΔT	10.9K	+13.5%/K	0.10K	1.35%	LM35C differential
P	101kPa	+0.0010%/Pa	1.5kPa	1.45%	MPXH6115A6U air pressure
C_{pt}	4.24kJ/K	+0.033%/(J/K)	42J/K	1.39%	plate thermal capacity
η	0.402	+208%	0.004	0.83%	anemometer calibration
C_V	1.000	−5.17%	0.100	0.52%	vertical reuptake
L_T	8.34mm	+7711%/m	100um	0.77%	post length
ς	2.00mm	−9801%/m	100um	0.98%	post height
D_{PIR}	25.4mm	−264%/m	1.0mm	0.26%	insulation thickness
L_m	3.57mm	+566%/m	500um	0.28%	side metal strip width
k_{PIR}	22.2 $\frac{mW}{K \cdot m}$	+0.262%/ $\frac{mW}{K \cdot m}$	1.1 $\frac{mW}{K \cdot m}$	0.29%	PIR thermal conductivity
ϵ_{tp}	0.890	+16.2%	0.015	0.24%	tape emissivity
Ω_{tp}	0.540	+11.0%	0.020	0.22%	tape coverage
ϵ_{rs}	0.040	+56.5%	0.010	0.56%	test-surface emissivity
ϵ_{wt}	0.900	+26.3%	0.025	0.66%	wind-tunnel emissivity
				3.09%	combined bias uncertainty
Symbol	Nominal	Sensitivity	Variability	Uncertainty	Component
ω	226r/min	+0.369%/(r/min)	1.8r/min	0.65%	fan rotation rate
				3.36%	RSS combined uncertainty


20180617T201351Z – mixed Convection – Roughness=1.04mm; T=18.0+10.2°C; +0.00°
320±0.9r/min, V=1.1m/s, Re=22871, Ra/L^3=1.037x10^9, h=12.6W/(K.m^2), U=1.17W/K, Nu=150.8



Estimated measurement uncertainties, bi-level 1mm roughness at $Re = 22870$.

Symbol	Nominal	Sensitivity	Bias	Uncertainty	Component
ΔT	10.2K	+13.2%/K	0.10K	1.32%	LM35C differential
P	101kPa	+0.0009%/Pa	1.5kPa	1.37%	MPXH6115A6U air pressure
C_{pt}	4.24kJ/K	+0.031%/(J/K)	42J/K	1.30%	plate thermal capacity
η	0.402	+202%	0.004	0.81%	anemometer calibration
C_V	1.000	−3.86%	0.100	0.39%	vertical reuptake
L_T	8.34mm	+8450%/m	100um	0.84%	post length
ς	2.00mm	−7103%/m	100um	0.71%	post height
D_{PIR}	25.4mm	−206%/m	1.0mm	0.21%	insulation thickness
L_m	3.57mm	+500%/m	500um	0.25%	side metal strip width
k_{PIR}	22.2 $\frac{mW}{K \cdot m}$	+0.206%/ $\frac{mW}{K \cdot m}$	1.1 $\frac{mW}{K \cdot m}$	0.23%	PIR thermal conductivity
ϵ_{rs}	0.040	+43.1%	0.010	0.43%	test-surface emissivity
ϵ_{wt}	0.900	+20.1%	0.025	0.50%	wind-tunnel emissivity
				2.84%	combined bias uncertainty
Symbol	Nominal	Sensitivity	Variability	Uncertainty	Component
ω	320r/min	+0.254%/(r/min)	0.92r/min	0.23%	fan rotation rate
				2.88%	RSS combined uncertainty


20180617T182712Z – mixed Convection – Roughness=1.04mm; T=17.9+10.1°C; +0.00°
465±14.0r/min, V=1.6m/s, Re=32463, Ra/L^3=1.030x10^9, h=16.7W/(K.m^2), U=1.55W/K, Nu=199.8



Estimated measurement uncertainties, bi-level 1mm roughness at $Re = 32461$.

Symbol	Nominal	Sensitivity	Bias	Uncertainty	Component
ΔT	10.1K	+12.4%/K	0.10K	1.24%	LM35C differential
P	101kPa	+0.0009%/Pa	1.5kPa	1.30%	MPXH6115A6U air pressure
C_{pt}	4.24kJ/K	+0.029%/(J/K)	42J/K	1.22%	plate thermal capacity
η	0.402	+188%	0.004	0.75%	anemometer calibration
C_V	1.000	-2.88%	0.100	0.29%	vertical reuptake
L_T	8.34mm	+8862%/m	100um	0.89%	post length
ς	2.00mm	-4608%/m	100um	0.46%	post height
L_m	3.57mm	+459%/m	500um	0.23%	side metal strip width
ϵ_{rs}	0.040	+32.2%	0.010	0.32%	test-surface emissivity
ϵ_{wt}	0.900	+15.0%	0.025	0.37%	wind-tunnel emissivity
				2.62%	combined bias uncertainty
Symbol	Nominal	Sensitivity	Variability	Uncertainty	Component
ω	465r/min	+0.162%/(r/min)	14r/min	2.27%	fan rotation rate
				5.24%	RSS combined uncertainty


20180617T163658Z – mixed Convection – Roughness=1.04mm; T=17.9+10.0°C; +0.00°
640±4.4r/min, V=2.1m/s, Re=42966, Ra/L^3=1.018x10^9, h=21.3W/(K.m^2), U=1.98W/K, Nu=254.9



Estimated measurement uncertainties, bi-level 1mm roughness at $Re = 42969$.

Symbol	Nominal	Sensitivity	Bias	Uncertainty	Component
ΔT	10.00K	+12.1%/K	0.10K	1.21%	LM35C differential
P	101kPa	+0.0008%/Pa	1.5kPa	1.25%	MPXH6115A6U air pressure
C_{pt}	4.24kJ/K	+0.028%/(J/K)	42J/K	1.18%	plate thermal capacity
η	0.402	+171%	0.004	0.69%	anemometer calibration
u_u	5.249	+2.47%	0.100	0.25%	diffuser airflow upper bound
C_V	1.000	-2.29%	0.100	0.23%	vertical reuptake
L_T	8.34mm	+9060%/m	100um	0.91%	post length
ς	2.00mm	-3027%/m	100um	0.30%	post height
L_m	3.57mm	+447%/m	500um	0.22%	side metal strip width
ϵ_{rs}	0.040	+25.6%	0.010	0.26%	test-surface emissivity
ϵ_{wt}	0.900	+11.8%	0.025	0.30%	wind-tunnel emissivity
				2.50%	combined bias uncertainty
Symbol	Nominal	Sensitivity	Variability	Uncertainty	Component
ω	640r/min	+0.107%/(r/min)	4.4r/min	0.47%	fan rotation rate
				2.67%	RSS combined uncertainty


20180617T144038Z – mixed Convection – Roughness=1.04mm; T=17.8+09.9°C; +0.00°
905±6.0r/min, V=2.8m/s, Re=56622, Ra/L^3=1.008x10^9, h=27.8W/(K.m^2), U=2.58W/K, Nu=332.7



Estimated measurement uncertainties, bi-level 1mm roughness at $Re = 56627$.

Symbol	Nominal	Sensitivity	Bias	Uncertainty	Component
ΔT	9.87K	+11.8%/K	0.10K	1.18%	LM35C differential
P	101kPa	+0.0008%/Pa	1.5kPa	1.22%	MPXH6115A6U air pressure
C_{pt}	4.24kJ/K	+0.027%/(J/K)	42J/K	1.15%	plate thermal capacity
η	0.402	+145%	0.004	0.58%	anemometer calibration
u_u	5.249	+4.21%	0.100	0.42%	diffuser airflow upper bound
L_T	8.34mm	+9187%/m	100um	0.92%	post length
L_m	3.57mm	+445%/m	500um	0.22%	side metal strip width
ϵ_{rs}	0.040	+20.5%	0.010	0.21%	test-surface emissivity
ϵ_{wt}	0.900	+9.45%	0.025	0.24%	wind-tunnel emissivity
				2.42%	combined bias uncertainty
Symbol	Nominal	Sensitivity	Variability	Uncertainty	Component
ω	905r/min	+0.066%/(r/min)	6.0r/min	0.39%	fan rotation rate
				2.55%	RSS combined uncertainty


20180617T124722Z – mixed Convection – Roughness=1.04mm; T=17.7+09.7°C; +0.00°
1280±7.3r/min, V=3.5m/s, Re=71949, Ra/L^3=0.993x10^9, h=34.3W/(K.m^2), U=3.19W/K, Nu=411.2



Estimated measurement uncertainties, bi-level 1mm roughness at $Re = 71950$.

Symbol	Nominal	Sensitivity	Bias	Uncertainty	Component
ΔT	9.69K	+11.8%/K	0.10K	1.18%	LM35C differential
P	101kPa	+0.0008%/Pa	1.5kPa	1.20%	MPXH6115A6U air pressure
C_{pt}	4.24kJ/K	+0.027%/(J/K)	42J/K	1.12%	plate thermal capacity
η	0.402	+110%	0.004	0.44%	anemometer calibration
u_u	5.249	+6.71%	0.100	0.67%	diffuser airflow upper bound
L_T	8.34mm	+9263%/m	100um	0.93%	post length
L_m	3.57mm	+447%/m	500um	0.22%	side metal strip width
				2.41%	combined bias uncertainty
Symbol	Nominal	Sensitivity	Variability	Uncertainty	Component
ω	1.28kr/min	+0.041%/(r/min)	7.3r/min	0.30%	fan rotation rate
				2.48%	RSS combined uncertainty

20180617T033137Z – mixed Convection – Roughness=1.04mm; T=17.8+09.6°C; +0.00°
1500±4.8r/min, V=3.9m/s, Re=79911, Ra/L^3=0.976x10^9, h=37.5W/(K.m^2), U=3.49W/K, Nu=449.3



Estimated measurement uncertainties, bi-level 1mm roughness at $Re = 79906$.

Symbol	Nominal	Sensitivity	Bias	Uncertainty	Component
ΔT	9.59K	+11.8%/K	0.10K	1.18%	LM35C differential
P	101kPa	+0.0008%/Pa	1.5kPa	1.20%	MPXH6115A6U air pressure
C_{pt}	4.24kJ/K	+0.026%/(J/K)	42J/K	1.11%	plate thermal capacity
η	0.402	+88.4%	0.004	0.36%	anemometer calibration
u_u	5.249	+8.30%	0.100	0.83%	diffuser airflow upper bound
L_T	8.34mm	+9289%/m	100um	0.93%	post length
L_m	3.57mm	+449%/m	500um	0.22%	side metal strip width
				2.44%	combined bias uncertainty
Symbol	Nominal	Sensitivity	Variability	Uncertainty	Component
ω	1.50kr/min	+0.039%/(r/min)	4.8r/min	0.19%	fan rotation rate
				2.46%	RSS combined uncertainty