

Out in the World: What Did The Robot Hear And See?

Lijin Aryananda

MIT CSAIL, 32 Vassar St Rm 380, Cambridge, MA 02139, lijin@csail.mit.edu

1. Introduction

In this paper, we present preliminary results obtained during the early development phase of a humanoid head robot, MERTZ, to explore socially situated learning. Inspired by the infant’s learning process, we strongly emphasize the role of experience in the world and social interaction, which are likely to be crucial to the development of human intelligence (Vygotsky, 1978). Given these biases, we propose that the robot must be able to operate in human spaces and time scales, continuously running every-day in different locations, and interact with many passersby. The idea is to move toward a robotic creature that *lives* around people on a regular basis and incrementally learns from its experience instead of a research tool for a specific task that interfaces only with its programmers within short-term testing periods. Starting with a set of *innate* behaviors and drive, i.e. preference for faces etc, we plan to explore the tasks of unsupervised individual recognition and lexical acquisition of socially relevant words.

Developmental approaches to robotics have been explored by many researchers, as surveyed in (Lungarella et al., 2004). The importance of social interaction for the robot learning framework was proposed in (Dautenhahn, 1995) and have been implemented in many platforms (Fong et al., 2003). The target task of word learning in robots through interaction with humans have also been explored in (Roy et al., 2002, Steels et al., 2001).

In (Aryananda et al., 2004), we report on design steps and issues involving the challenge of achieving reliable continuous operation. In this paper, we address the equally challenging objective of generating social feedback from humans which would be crucial to the robot’s learning process. In particular, we analyze the feasibility for learning to recognize individuals and acquire lexicon of relevant words through social interaction. To this end, we have developed the perceptual and behavior systems to engage in simple visual and verbal interaction. The robot tracks salient visual targets (faces and bright objects) and tries to encourage verbal interaction by mimicking phoneme sequences extracted from speech input.

We conducted an experiment where the robot ran




Figure 1. MERTZ, an active-vision humanoid head robot, mounted on a portable platform.

for 7 hours/day for 5 days at different locations on the 1st floor of the laboratory building (Stata Center), to address the following questions:

Will people interact with the robot enough to acquire a set of training face images for further recognition? Are people going to speak to the robot? Will they use enough one-word utterances to avoid the difficult word segmentation task? Will there be enough word repeatability for the robot to acquire a lexicon of socially relevant words?

2. Robotic System

MERTZ is an active-vision head robot with thirteen degrees of freedom (see Figure 1), two digital cameras, and a voice array desk microphone. The robot’s visual system¹ is equipped with detectors for skin and saturated color, motion, and face (Viola et al., 2001). These detectors are complemented with a KLT-based face tracker (Shi et al., 1994) and a color-histogram tracker. The audio system consists of a phoneme recognizer (Mosur) and the DECtalk speech synthesizer. More implementation details are described in (Aryananda et al., 2004)

3. Experimental Results

What did the robot see? We labelled the tracker’s output from a sequence of 14186 frames collected during a 4-hour period on day 2 (see Figure 2 Top) For 16.9% of the time, the robot tracked correctly segmented faces. For a small part of the time, the robot tracked partially segmented faces

¹The visual system is implemented using YARP (<http://sourceforge.net/projects/yarp0>)




Figure 2. Top: The characteristic of speech input received by the robot on each day of the experiment. Bottom: The face detector's accuracy over 114,880 faces detected in 4 days and a sample set of the 94,426 correctly detected faces.




Figure 3. Left: The characteristic of speech input received by the robot on each day of the experiment. Right: Pitch average and gradient values from robot and non-robot directed speech.

and bright objects. We also collected every frame of detected faces throughout the experiment, which amount to 114,880 images from at least 600 individuals. Figure 2 Bottom shows the detector's accuracy during each day, excluding one due to file loss. These results suggest that it is feasible to acquire a significant set of face images because people do interact with the robot closely and for long enough durations.

What did the robot hear? The robot received over 1000 utterances (segmented using energy threshold) per day. We transcribed 3027 audio samples recorded from at least 200 speakers, taken from a few continuous sequences of speech input spanning several hours each day. As shown in Figure 3 Left, approximately 37% of the total utterances are intelligible robot directed speech. Figure 4 Top shows that one-word utterances make up 38% of all intelligible speech and 38.6% of robot directed speech. Approximately 83.2% of all intelligible speech and 87.8% of robot directed speech contain less than 5 words. Figure 4 Bottom illustrates the top fifteen




Figure 4. Top: Number of words/utterance collected on day 1&2. Bottom: The top 15 most frequent words

most frequently said words during each experiment day. Figure 3 Right illustrates that average pitch of female and male speakers is higher when speaking to the robot versus other people. The pitch gradient data suggests that female speakers produce more modulated pitch contours when speaking to the robot. These results suggest that people do verbally interact with the robot. The frequency of one-word utterances seems to be high enough to provide the robot with a starting point for unsupervised lexical acquisition. Lastly, a set of common words tend to be repeated throughout the experiment despite the large number of speakers and minimal constraints on the human-robot interaction.

References

- L. Aryananda, J. Weber. Mertz: A Quest for a Robust and Scalable Active Vision Humanoid Head Robot. *IEEE-RAS/RSJ International Conference on Humanoid Robots*, 2004.
- K. Dautenhahn. Getting to Know Each Other-Artificial Social Intelligence for Autonomous Robots. *Robotics and Autonomous Systems*, 16:333-356, 1995.
- T. Fong, I. Nourbakhsh, and K. Dautenhahn. A Survey of Socially Interactive Robots. *Robotics and Autonomous Systems*, 42:143-166, 2003.
- M. Lungarella, G. Metta, R. Pfeifer, and G. Sandini. Developmental Robotics: A Survey. *Connection Science*, vol.00 no.0:1-40, 2004.
- R. Mosur. <http://cmusphinx.sourceforge.net/sphinx2>.
- D. Roy and A. Pentland. Learning Words From Sights and Sounds: A Computation Model. *Cognitive Science*, 26(1):113-146, 2002.
- J. Shi and C. Tomasi. Good features to track. *IEEE Conference on Computer Vision and Pattern Recognition*, pp 593-600, 1994.
- L. Steels and F. Kaplan. Aibo's First words. The Social Learning of Language and Meaning. *Evolution of Communication*, 4(1), 2001.
- P. Viola and M. Jones. Robust Real-time Object Detection. *Technical Report Series, CRL2001/01. Cambridge Research Laboratory*, 2001.
- L. Vygotsky. Mind in Society. *Cambridge, MA: Harvard Univ Press*, 1978.