

TO: Distribution
FROM: George T. Williams
DATE: December 27, 1976
SUBJECT: Installation of BOS 2.06, 2.06a

I. SYSTEM CHANGE LOG

MCR MODIFICATIONS FOR BOS 2.06 2.06a

- 2203 The "." processor in PATCH is fixed to properly save the address previously requested.
- 2170 Implements a mechanism to allow BOS to determine if an emergency shutdown is required after a system crash.
- 2171 Modifies the syntax of the BOS IF command.
- 2356 Fix the BOSTAP control word bug. Stop writing meaningless control word at the end of BOS tapes.
- 1534 Put continuous operation (auto reboot) runcoms on tape. Expands communication between BOS and Multics to support automatic recovery mode.
- 1923 Changed the BOS SST name table filler to walk the AST ASTE by ASTE, Removes the tree walk of the AST.

II. SEGMENT CHANGE LOG

SEGMENT NAME

blast.alm	R -
boot.alm	R -
fd355.alm	R -
if.alm	R -
ld355.alm	R -
ntaoe.alm	R -
patch.alm	R -
ptpkg.alm	R -
setup.alm	R -

Multics Project Internal documentation. Not to be reproduced or distributed outside the Multics Project.

II. SEGMENT CHANGE LOG (continued)

SEGMENT NAME

time.alm	R -
util.alm	R -
bostap.alm	R -
auto.ascii	A -
restar.ascii	A -
rtb.ascii	A -
crash.ascii	A -
tryagn.ascii	A -
tdump.ascii	A -
boscal.ascii	A -
gog.ascii	A -
mrtb.ascii	A -
ngsw.ascii	A -
sstn.alm	R -

INCLUDE SEGMENTS

argmul.incl.alm	R
cvaad.incl.alm	R
rdclock.incl.alm	R
writape.incl.alm	R