

TO: Distribution
 FROM: George T. Williams
 DATE: May 25, 1977
 SUBJECT: Installation of BOS 2.09

I. SYSTEM CHANGE LOG

MCR MODIFICATIONS FOR BOS 2.09

- 2677 Improves operator's console primitives: (substantially less automatic storage required; newline output after reading or printing a line). <BOS PORTION OF INSTALLATION ONLY>
- 2663 A dual IOM firmware loading bug is fixed.
- 2662 Modifies the BOS IF command to allow crashes to be intercepted by runcoms even if they occur before the storage system is enabled.
- 2661 BOS SAVE is modified to save only those records in the paging area of a volume.
- 2622 Provides a mechanism to supply operator message instead of returning to BOS with no message. (ONLY THE BOS PORTION)
- 2520 Changes the BOS SAVE-tape reading module, NTAPE, to respect Multics Standard Tape End-of-reel (EOR).

II. SEGMENT CHANGE LOG

SEGMENT NAME

fwload.alm	R
if.alm	R
loaddm.alm	R
ntape.alm	R
rtb.ascii	R
save.alm	R
setup.alm	R
util.alm	R

Multics Project internal documentation. Not to be reproduced or distributed outside the Multics Project.

II. SEGMENT CHANGE LOG (continued)

INCLUDE SEGMENTS

bos_toegu.incl.alm	R
error.incl.alm	R
fobx.incl.alm	R (1)
getportinfo.incl.alm	R
readt.incl.alm	R

(1) replaced in >ldd>include