

TO: Distribution
 FROM: George T. Williams
 DATE: June 23, 1977
 SUBJECT: Installation of MSS 31.6

I. SYSTEM CHANGE LOG

MCR MODIFICATIONS FOR MSS 31.6

- 2664 Allow up to 52 subchannels per LSLA
- 2703 Adds an unwired data base to Ring 0 MCS. (One part of the plan to implement installation defined terminal types.)
- 2488 Hardcore portion of the line_control and line_status orders.

II. SEGMENT CHANGE LOG

SEGMENT NAME		BOUND SEGMENT
dn355.pl1	R	bound_355_wired
error_table_.alm	R	-
fnp_util.pl1	R	bound_mcs_util
hardcore.header	R	-
load_fnp_.pl1	R	bound_mcs_init_
terminate_proc.pl1	R	bound_error_active
tty_assign.pl1	R	bound_mcs_util
tty_free.pl1	R	bound_355_wired
tty_index.pl1	R	bound_tty_active
tty_init_.pl1	R	bound_mcs_init_
tty_lock.pl1	R	bound_355_wired
tty_read.pl1	R	bound_tty_active
tty_write.pl1	R	bound_tty_active

Multics Project internal documentation. Not to be reproduced or distributed outside the Multics Project.

II. SEGMENT CHANGE LOG (continued)

BIND SEGMENTS

bound_355_wired.bind	R
----------------------	---

INCLUDE SEGMENTS

mailbox_ops.incl.pl1	R
terminal_info.incl.pl1	A
terminal_type_data.incl.pl1	A
tty_buf.incl.pl1	R
tty_data.incl.pl1	R
tty_event_message.incl.pl1	R
tty_tables.incl.pl1	A