

TO: Distribution
FROM: Peter B. Kelley
DATE: June 21, 1974
SUBJECT: Installation of MSS 23.12
This supersedes MIB-100

The hardcore system MSS 23.12 was installed at 0900 on Friday, June 21, 1974. This system includes: a new mode "writew" (write wait) for T & D; a new PRPH config. card format; a new TBLs config. card; new operator console software; provision of optional command usage monitoring; and, several bug fixes. The system libraries were updated at 1210 on June 21, 1974.

I. System Change Log

Chng MCR

Change

- # 1311 315,464,498,517
adds new mode "writew" for T & D; fixes 2 cpu bug in tty_inter; fixes bug which caused \014's to be lost when typed as the last character of a line; and, fixes hangup problem in conjunction with system control (1317).
- # 1312 391,406,414,454
new PRPH config. card format (MOSN 4.3.2); and, new operator console software for the operation of the System Control Console and Entry Module Console.
- # 1313 551 fixes bug to reset the default device type of a terminal based on the baud rate whenever a terminal hangs up.
- # 1314 435 Introduces TBLs config. card to allow boot-time specification of the size of the ioat, str_seg, and paged_tape_data system data bases. Defaults for these are provided by the cur_length attribute of the hardcore header.
- # 1315 412 Provides optional command usage monitoring under the control of the tool command_usage_count.

Multics Project internal documentation. Not to be reproduced or distributed outside the Multics Project.

I. System Change Log (continued)

Chng MCR

Change

- # 1316 507 Adds the two error table codes \$chars_after_delim, and \$no_delimiter.
- # 1317 520 updates a branch so that correct length of a segment will be correct before making a copy when initiating a segment with the copy switch.
- # 1318 305,427
new version of system control to eliminate problems with "sac" and misuse of global variables. Implements input logging of operator commands, and "intercom" command.
- # 1319 548 fixes bug in tty_free which caused a free chain call to fail if the first buffer in tty_buf was in the chain.

II. Segment Change Log

| Segment Name | Bound Segment | Change # |
|---------------------|---------------------|-------------|
| config.pl1 | bound_active_1 | A 1312 |
| error_table.et | - | R 1316 |
| find.pl1 | bound_active_1 | D 1312 |
| find_command.pl1 | bound_command_loop_ | R 1315 |
| find_peripheral.pl1 | bound_active_1 | D 1312 |
| init_str_seg.pl1 | bound_temp_2 | R 1314 |
| initiate.pl1 | bound_system_faults | R 1317 |
| make_sdw.pl1 | bound_init_1 | R 1314 |
| oc_data.alm | - | R 1312 |
| oc_data_init.pl1 | bound_temp_1 | R 1312 |
| oc_trans_input.pl1 | bound_oc_ | R 1312 |
| oc_trans_output.pl1 | bound_sss_wired_ | R 1312 |
| ocdcn.pl1 | bound_error_wired | R 1312 |
| ocdim.pl1 | bound_oc_ | R 1318 |
| rest_of_ttydim.pl1 | bound_command_loop_ | R 1311 |
| system_control.pl1 | - | R 1318 |
| tape_init.pl1 | bound_io_init | R 1312 |
| tty_ctl.ioc | - | R 1311 |
| tty_free.pl1 | bound_iom_wired | R 1319 |
| tty_index.pl1 | bound_tty_active | R 1311 |
| tty_inter.pl1 | bound_iom_wired | R 1311,1313 |
| tty_write.pl1 | bound_tty_active | R 1311 |

II. Segment Change Log (continued)

| <u>Segment Name</u> | <u>Bounc Segment</u> | <u>Change #</u> |
|--------------------------|----------------------|-----------------|
| <u>Include Files</u> | | |
| command_usage.incl.pl1 | | A 1315 |
| convtab.incl.pl1 | | R 1311 |
| oc_data.incl.pl1 | | R 1312 |
| fab.incl.ioc | | R 1311 |
| tty.incl.pl1 | | R 1311 |
| variable_tables.incl.pl1 | | R 1311 |
| | | A 1314 |
| <u>Bindfiles</u> | | |
| bounc_active_1.bind | | R 1312 |
| bounc_error_wired.bind | | R 1312 |

III. Bounc Segment Change Log

| <u>Bounc Segment</u> | <u>Change</u> |
|----------------------|---|
| bounc_init_1 | replaced: make_sdw |
| bounc_temp_2 | replaced: init_str_seg |
| bounc_command_loop_ | replaced: find_command_ rest_of_ttydim_ |
| bounc_active_1 | added: config deleted: find find_peripheral |
| bounc_temp_1 | replaced: oc_data_init |
| bounc_oc_ | replaced: occim_ oc_trans_input_ |
| bounc_sss_wired_ | replaced: oc_trans_output_ |
| bounc_error_wired | replaced: ocpcm_ |
| bounc_io_init | replaced: tape_init |
| bounc_system_faults | replaced: initiate |
| bounc_lom_wired | replaced: tty_free tty_inter |
| bounc_tty_active | replaced: tty_write tty_index |

IV. Header Change Log

1312 The header was changed to add the entry name find_periph
to bound_active_1.