

# Open Problems from Dagstuhl Seminar 16451: Structure and Hardness in P

Organizers: Moshe Lewenstein, Seth Pettie, Virginia Vassilevska Williams

The Dagstuhl Seminar *Structure and Hardness in P* took place November 7-11, 2016. The following open problems were contributed by the seminar attendees, and compiled and edited by the organizers.

## Open Problem 1: Parameterizing problems in P by treewidth

**Background.** Let  $t$  be the treewidth of an input graph. Many NP-hard problems, particularly those expressible in MSOL, are solvable in  $f(t)n$  time and there are lower bounds on the (exponential) function  $f$  conditioned on the Strong Exponential Time Hypothesis (SETH) [26]. For problems in P the picture is less clear. Consider your favorite problem  $\Pi$  in P solvable in  $T_\Pi(n)$  time on a graph with  $n$  vertices. Some problems  $\Pi$  admit algorithms running in  $\text{poly}(t) \cdot o(T_\Pi(n))$  time whereas others do not. For example, Abboud et al. [5] proved that *Diameter* can be solved in  $2^{O(t \log t)} n^{1+o(1)}$  time, yet a  $2^{o(t)} n^{2-\epsilon}$  time algorithm would refute SETH. On the other hand, *maximum cardinality matching* can be solved in randomized  $O(t^3 \cdot n \log n)$ -time [31].

**Question.** Classify graph problems in P according to their dependence on treewidth. Which problems admit  $f(t) \cdot n^{1+o(1)}$ -time algorithms with polynomial  $f$ , and which require exponential  $f$ ? A specific goal is to determine whether *maximum weight perfect matching* has an  $\tilde{O}(\text{poly}(t)n)$  algorithm, for integer weights from a polynomial range.

**Main paper reference:** Abboud et al. [5], Fomin et al. [31].

[Contributed by *Fedor V. Fomin*.]

## Open Problem 2: Approximate all-pairs shortest paths

**Background.** In unweighted, undirected graphs, we can compute All Pairs Shortest Paths (APSP) in  $O(n^3)$  time with a fast “combinatorial” algorithm, or in  $O(n^\omega)$  time, where  $\omega < 2.373$  is the matrix multiplication exponent. It is conjectured that a truly subcubic combinatorial algorithm does not exist, which is equivalent to the combinatorial Boolean matrix multiplication conjecture.

What about approximation algorithms? The best kind of approximation is an additive +2, so that for all pairs  $u, v$  we return a value that is between  $d(u, v)$  and  $d(u, v) + 2$ . Dor, Halperin, and Zwick [30] presented a *combinatorial* algorithm with runtime  $\tilde{O}(n^{7/3})$ . Note that this runtime is currently even better than  $O(n^\omega)$ , and has the advantage of being practical.

**Questions.** Is there a conditional lower bound for +2-APSP? Can we show that a combinatorial algorithm must spend  $n^{7/3-o(1)}$  time? Would a faster non-combinatorial algorithm require improvements to  $\omega$ ? Alternatively, is there an  $\tilde{O}(n^2)$  time algorithm for +2-APSP?

**Main paper reference:** Dor, Halperin, and Zwick [30].

[Contributed by *Amir Abboud*.]

### Open Problem 3: Approximate diameter

**Background.** Computing the diameter of a sparse graph in truly subquadratic time refutes SETH: Roditty and Vassilevska Williams [62] showed that a  $(3/2-\varepsilon)$ -approximation to the diameter requires  $n^{2-o(1)}$  time, even on a sparse unweighted undirected graph under SETH. On the other hand, there are algorithms [62, 22] that give a (roughly)  $3/2$  approximation in  $\tilde{O}(m\sqrt{n})$  time on unweighted graphs, or  $\tilde{O}(\min\{m^{3/2}, mn^{2/3}\})$  time on weighted graphs. Extending these algorithms further, Cairo et al. [19] showed that for all integers  $k \geq 1$ , there is an  $\tilde{O}(mn^{1/(k+1)})$  time algorithm that approximates the diameter of an undirected unweighted graph within a factor of (roughly)  $2 - 1/2^k$ .

**Question.** If we insist on near-linear runtime, what is the best approximation factor we can get? It is easy to see that a 2-approximation can be achieved in linear time, but what about an  $\alpha$ -approximation, where  $3/2 \leq \alpha < 2$ ?

**Main paper reference:** Roditty and Vassilevska W. [62].

[Contributed by *Amir Abboud*.]

### Open Problem 4: Finding cycles and approximating the girth

**Background.** Consider an unweighted undirected graph  $G = (V, E)$ . The *girth* of  $G$  is the length of the shortest cycle. The problem of detecting 3-cycles (and odd cycles of any length) is reducible to matrix multiplication and there are reductions in the reverse direction; see [66]. Yuster and Zwick [67] showed that detecting  $2k$ -cycles can be computed in  $O(f(k)n^2)$  time, where  $f$  is exponential.

**Question.** For any fixed constant  $k$ , give a conditional lower bound, showing that there does not exist an algorithm deciding whether  $G$  contains a  $2k$ -cycle in time  $O(f(k)n^{2-\varepsilon})$  for any  $\varepsilon > 0$ , or one running in  $O(f(k)m^{2k/(k+1)-\varepsilon})$  time, where  $m$  is the number of edges.

**Main paper reference:** Yuster and Zwick [67].

**Question.** Prove or disprove the following conjecture: There exists a truly subquadratic algorithm for finding a 4-cycle in a graph if and only if there exists a truly subquadratic algorithm for finding a multiplicative  $(2 - \epsilon)$ -approximation of the girth.

**Question.** Prove or disprove the following conjecture from [63]: the problem of detecting a 3-cycle in a graph  $G$  without 4- and 5-cycles requires  $n^{2-o(1)}$  time. Note that if there exists a subquadratic  $(2 - \epsilon)$ -approximation for the girth, it must be able to detect 3-cycles in graphs without 4- and 5-cycles. See [63] for more details.

**Main paper reference:** Roditty and Vassilevska W. [63].

[Contributed by *Mathias Bæk Tejs Knudsen and Liam Roditty.*]

### Open Problem 5: Minimum cycle problem in directed graphs

**Background.** Given an unweighted *directed* graph  $G = (V, E)$  on  $n$  vertices, the problem is to find a shortest cycle in  $G$ . The potentially simpler *Girth* problem asks to compute just the length of the shortest cycle.

The girth and the minimum cycle can be computed in  $O(n^\omega)$  time exactly, as shown by Itai and Rodeh [49], where  $\omega < 2.373$ . It is easy to see that the minimum cycle problem is at least as hard as finding a triangle in a graph. In fact, even obtaining a  $(2 - \delta)$ -approximation for the girth for any constant  $\delta > 0$  is at least as hard as triangle detection. The fastest algorithm for the Triangle problem in  $n$  node graphs runs in  $O(n^\omega)$  time.

**Question.** Is there any  $O(1)$ -approximation algorithm for the girth that runs faster than  $O(n^\omega)$  time? In recent work, Pachocki, Roditty, Sidford, Tov, and Vassilevska Williams [59] showed that for any integer  $k$ , there is an  $\tilde{O}(mn^{1/k})$  time  $O(k \log n)$  approximation algorithm for the Minimum Cycle problem. Thus, in nearly linear time, one can obtain an  $O(\log^2 n)$ -approximation. Can one improve the approximation factor further? Can one even obtain a constant factor approximation in linear time?

**Main paper reference:** Pachocki et al. [59].

[Contributed by *Virginia Vassilevska Williams.*]

### Open Problem 6: Linear Programming

**Background.** Consider a linear program of the following form: minimize  $c^T x$  subject to  $Ax \geq b$ , where  $A$  is an  $d$ -by- $n$  constraint matrix. Suppose that we could solve any such LP in time

$$\tilde{O}\left(\left(\text{nnz}(A) + d^2\right) d^\delta \log L\right),$$

where  $\text{nnz}(A)$  is the number of non-zero entries of  $A$ ,  $L$  is the bound on the bit complexity of the input entries, and  $\delta$  is a positive constant.

**Question.** Is there some value of  $\delta$  for which the above (hypothetical) running time bound would disprove any of the popular hardness conjectures?

In [57], it is shown that one can achieve the above running time bound for  $\delta = \frac{1}{2}$ .

**Main paper reference:** Lee and Sidford [57].

[Contributed by *Aleksander Madry*.]

## Open Problem 7: Fully dynamic APSP

**Background.** In the fully dynamic all-pairs shortest paths (APSP) problem we are interested in maintaining the distance matrix of a graph under insertions and deletions of nodes. Demetrescu and Italiano [28] showed that the distance matrix can be updated in *amortized* time  $\tilde{O}(n^2)$  after each node update. The current fastest *worst case* algorithms have update times of  $\tilde{O}(n^{2+2/3})$  (randomized Monte Carlo [7]) and  $\tilde{O}(n^{2+3/4})$  (deterministic [65]).

**Questions.** Can the worst case update time  $\tilde{O}(n^2)$  be achieved? A barrier for current algorithmic approaches is  $n^{2.5}$ . Is there a conditional lower bound showing this to be a true barrier?

**Main paper reference:** Abraham et al. [7].

[Contributed by *Sebastian Krinninger*.]

## Open Problem 8: Dynamic reachability in planar graphs

**Background.** *Dynamic reachability* in a planar graph  $G$  is the problem of maintaining a data structure supporting the following operations: (i) Insert a directed edge  $(u, v)$  into  $G$ , (ii) delete an edge from  $G$ , and (iii) query whether  $v$  is reachable from  $u$  in  $G$ .

An algorithm with update and query time  $\tilde{O}(\sqrt{n})$  is known (Diks and Sankowski [29]) for dynamic *plane graphs*—that is, the graph is dynamic but the plane embedding is fixed.

**Question.** Does an  $n^{1/2-\Omega(1)}$  algorithm exist or is there a conditional  $n^{1/2-o(1)}$  hardness result? Any polynomial hardness result would be interesting. A good place to start for the latter part would be the recent paper by Abboud and Dahlgaard [3] about hardness for dynamic problems in planar graphs.

**Main paper reference:** Abboud and Dahlgaard [3].

[Contributed by *Søren Dahlgaard*.]

## Open Problem 9: Static hardness for planar graphs

**Background.** An important direction is to show conditional hardness for important problems, even on restricted (easier) classes of graphs, e.g., planar graphs. Abboud and Dahlgaard [3] recently showed hardness for several *dynamic* problems in planar graphs, but nothing is known for static problems.

**Question.** On planar graphs, many problems (such as shortest paths, multi-source multi-sink max-flow, etc.) run in near-linear time. Can we show that some problem does not? No hardness results are known for any static problem in  $\mathbf{P}$  on planar graphs. Two candidate problems to consider are *diameter* and *sum of distances*. Both require subquadratic time (Cabello [18]), but it may still be possible to show a hardness result, e.g.,  $n^{3/2-o(1)}$  hardness.

**Main paper reference:** Cabello [18].

[Contributed by *Søren Dahlgaard*.]

## Open Problem 10: Sparse reductions for graph problems

**Background.** Many graph problems are known to be as hard as APSP on dense graphs [66, 4, 64], in the sense that a subcubic algorithm for any of them implies a subcubic algorithm for all of them. When the graph sparsity is taken into account, these problems currently are no longer in a single class: many have  $\tilde{O}(mn)$ -time algorithms whereas finding minimum weight triangle and related problems have  $\tilde{O}(m^{3/2})$ -time algorithms. Most known fine-grained reductions between graph problems do not preserve the graph sparsity. Until recently, the only examples of sparseness-preserving truly subcubic reductions appeared in [4]. Agarwal and Ramachandran [8] presented several more such reductions, strengthening the connections between problems with  $\tilde{O}(mn)$ -time algorithms. A reduction from CNF-SAT to Diameter was presented in [62] to give SETH-hardness results for Diameter and Eccentricities. The notion of a *sub- $mn$  time bound* was formalized later, in [8], where it was observed that the reduction in [62] gives SETH-hardness for any sub- $mn$  time bound for these problems.

**Questions.** Is there a sparseness-preserving,  $\tilde{O}(n^2)$  time reduction from undirected weighted All Nodes Shortest Cycles (ANSC) to APSP? Is there a sparseness-preserving,  $\tilde{O}(m+n)$  time reduction from undirected Min-Wt-Cycle to either Radius or Eccentricities? Is it SETH-hard to find a sub- $mn$  bound for Min-Wt-Cycle or an  $O(n^2 + \text{sub-}mn)$  bound on APSP?

**Main paper reference:** Agarwal and Ramachandran [8].

[Contributed by *Vijaya Ramachandran*.]

## Open Problem 11: Hardness for partially dynamic graph problems

**Background.** Many results show hardness for *fully*-dynamic problems in graphs, but the techniques do not seem to extend well to amortized lower bounds in the incremental and decremental cases. (See Abboud and Vassilevska Williams [2], Henzinger, Krinninger, Nanongkai, and Saranurak [46], Kopelowitz, Pettie and Porat [55], and Dahlgaard [27] for some initial results on incremental/decremental problems.)

**Question.** Develop general techniques for showing amortized hardness of partially dynamic problems in graphs. One candidate problem is decremental single-source reachability. A result of Chechik, Hansen, Italiano, Lacki, and Parotsidis [23] shows that  $\tilde{O}(m\sqrt{n})$  total time is sufficient. Is it necessary?

[Contributed by *Søren Dahlgaard*.]

## Open Problem 12: Hardness of vertex connectivity

**Background.** A connected undirected graph is  $k$ -vertex (resp. edge) connected if it remains connected after any set of at most  $k - 1$  vertices (edges) is removed from the graph. A strongly connected directed graph is  $k$ -vertex (edge) connected if it remains strongly connected after any set of at most  $k - 1$  vertices (edges) is removed from the graph. The vertex (edge) connectivity of a graph is the maximum value of  $k$  such that the graph is  $k$ -vertex (edge) connected.

The edge-connectivity  $\lambda$  of an undirected graph can be determined in time  $O(m \log^2 n \log^2 \log n)$  [47, 54], and for directed graphs in time  $O(\lambda m \log(n^2/m))$  [37]. In contrast, the vertex-connectivity  $\kappa$  can only be computed in time  $O((n + \min\{\kappa^{5/2}, \kappa n^{3/4}\})m)$  [38], where for undirected graphs  $m$  can be replaced by  $kn$ .

**Question.** To *check*  $k$ -vertex connectivity means to either confirm that  $\kappa \geq k$  or to find a set of  $k - 1$  vertices that disconnects the graph. Even when  $k$  is constant, no  $o(n^2)$  time (or  $o(mn)$  time for directed graphs) algorithms are known for checking  $k$ -connectivity. Is there a conditional superlinear lower bound?

**Main paper reference:** Gabow [38].

[Contributed by *Veronika Loitzenbauer*.]

### Open Problem 13: Parity and mean-payoff games

**Background.** *Parity games*, and their generalization *mean-payoff games*, are among the rare “natural” problems in  $\text{NP} \cap \text{co-NP}$  (and in  $\text{UP} \cap \text{co-UP}$  [52]) for which no polynomial-time algorithm is known. Both parity games and mean-payoff games are 2-player games played by taking an infinite walk on a directed graph; one of the vertices is designated the start vertex. In parity games each vertex is labeled by an integer in  $[0, c]$ ; in mean payoff games each edge is labeled by an integer in  $[-W, W]$ . (See [53] for a description of the game.) The algorithmic question is to decide, for each start vertex, which of the two players wins the game and to construct a corresponding winning strategy. Parity games can be reduced to mean-payoff games with  $W = n^c$ . Very recently, quasi-polynomial  $O(n^{\log c})$  time algorithms for parity games were discovered [20, 51]. The best known algorithms for mean-payoff games run in pseudo-polynomial time  $O(mnW)$  [16] and randomized sub-exponential time  $O(2^{\sqrt{n \log n}} \log W)$  [15].

**Questions.** Is there a polynomial-time algorithm for parity or mean-payoff games? Are there conditional superlinear lower bounds on these problems?

[Contributed by *Veronika Loitzenbauer*.]

### Open Problem 14: Unknotting

**Background.** A *knot* is a closed, non-self-intersecting polygonal chain in  $\mathbb{R}^3$ . Two knots are *equivalent* if one can be continuously deformed into the other without self-intersection. The *unknot* problem is to decide if a knot is equivalent to one that is embeddable in the plane.

Knots can be represented combinatorially, by projecting the polygonal chain onto  $\mathbb{R}^2$ , placing a vertex wherever two edges intersect. The result is a 4-regular planar graph (possibly with loops and parallel edges) where each vertex carries a bit indicating which pair of edges is “over” and which pair is “under.” *Reidemeister moves* (a small set of transformations on the knot diagram) suffice to transform any knot diagram to one of its equivalent representations.

The complexity of *unknot* and related problems (e.g., are two knots equivalent?, can two knots simultaneously embedded in  $\mathbb{R}^3$  be untangled?) are known to be in **NP** [45] and solvable in  $2^{O(n)}$  time [45, 50].

**Questions.** Given a plane knot diagram with  $n$  intersections, can *unknot* or *knot-equivalence* be solved in time near-linear in  $n$ ? If not, are there conditional lower bounds that show even some polynomial hardness?

[Contributed by *Seth Pettie*.]

## Open Problem 15: 3-Collinearity (general position testing)

**Background.** A set  $S$  of  $n$  points in  $\mathbb{R}^2$  is said to be in *general position* if there do not exist three points in  $S$  that lie on a line. The *3-Collinearity* problem is to test whether  $S$  is in general position. The 3-Collinearity problem is known to be as hard as 3SUM, and an algorithm that runs in  $O(n^2)$  time is known.

**Questions.** The question is whether the  $O(n^2)$  algorithm is optimal or whether it can be solved in  $o(n^2)$  time. Recent subquadratic algorithms for 3SUM [12, 44, 34, 41] indicate that polylogarithmic improvements should be possible. A related question is whether there is an  $O(n^{2-\epsilon})$ -depth decision tree for 3-Collinearity; see [44, 13].

**Main paper reference:** Gajentaan and Overmars [39].

[Contributed by *Omer Gold*.]

## Open Problem 16: Element uniqueness in $X + Y$

**Background.** Given two sets  $X$  and  $Y$ , each of  $n$  real numbers, determine whether all the elements of  $X + Y = \{x + y \mid x \in X, y \in Y\}$  are distinct. A somewhat stronger variant of this problem is to sort  $X + Y$ .

The decision tree complexity of sorting  $X + Y$  and Element Uniqueness in  $X + Y$  was shown to be  $O(n^2)$  by Fredman [33].

**Question.** Can these problems be solved in  $o(n^2 \log n)$  time, even for the special case  $X = Y$ ?

[Contributed by *Omer Gold*.]

## Open Problem 17: Histogram indexing

**Background.** The *histogram*  $\psi(T)$  of a string  $T \in \Sigma^*$  is a  $|\Sigma|$ -length vector containing the number of occurrences of each letter in  $T$ . The *histogram indexing problem* (aka *jumbled indexing*) is to preprocess a string  $T$  to support the following query: given a histogram vector  $\psi$ , decide whether there is a substring  $T'$  of  $T$  such that  $\psi(T') = \psi$ .

The state-of-the-art algorithm for histogram indexing [21] preprocesses a binary text  $T$  in  $O(n^{1.859})$  time and answers queries in  $O(1)$  time. Over a  $d$ -letter alphabet the preprocessing and query times are  $\tilde{O}(n^{2-\delta})$  and  $\tilde{O}(n^{2/3+\delta(d+13)/6})$ , for any  $\delta \geq 0$ . On the lower bound side [10, 42], the 3SUM conjecture implies that it is impossible to simultaneously improve  $n^{2-\delta}$  preprocessing and  $n^{\delta(d/2-1)}$  query time by polynomial factors, where  $\delta \leq 2/(d-1)$  and  $d \geq 3$ .

**Question.** Are there any non-trivial lower bounds on histogram indexing when  $d = 2$ ? Is it possible to close the gap between the lower and upper bounds in general, or to base the hardness off of a different conjecture than 3SUM?



**Main paper reference:** Chan and Lewenstein [21].

[Contributed by *Isaac Goldstein*.]

### Open Problem 18: Integer programming

**Background.** The objective of *Integer Programming* (IP) is to decide, for a given  $m \times n$  matrix  $A$  and an  $m$ -vector  $b = (b_1, \dots, b_m)$ , whether there is a non-negative integer  $n$ -vector  $x$  such that  $Ax = b$ . In 1981, Papadimitriou [61] showed that (IP) is solvable in pseudo-polynomial time on instances for which the number of constraints  $m$  is constant. The rough estimation of the running time of Papadimitriou's algorithm is  $n^{O(m)} \cdot d^{O(m^2)}$ , where  $d$  bounds the magnitude of any entry in  $A$  and  $b$ . The best known lower bound is  $n^{\omega(\frac{m}{\log m})} d^{\omega(m)}$  [32], assuming the Exponential Time Hypothesis (ETH).

**Question.** Is it possible to narrow the gap between algorithms for IP and the ETH-hardness of IP?

**Main paper reference:** Fomin et al. [32].

[Contributed by *Fedor V. Fomin*.]

### Open Problem 19: All-pairs min-cut and generalizations

**Background.** The *all-pairs min-cut* problem is, given an edge-capacitated undirected graph  $G = (V, E, c)$ , to compute the minimum  $s$ - $t$  cut over all pairs  $s, t \in V$ . Gomory and Hu [43] showed the problem is reducible to  $n-1$   $s$ - $t$  min-cut instances, and moreover, all  $\binom{n}{2}$  min-cuts can be represented by a capacitated tree  $T$  on the vertex set  $V$ . On unweighted graphs, the construction of  $T$  takes time  $\tilde{O}(mn)$  [14, 60].

Generalizations of this problem include finding the min-cut separating every triple  $(r, s, t) \in V^3$ , which is **NP**-hard, and finding the min-cuts separating all pairs of  $k$ -sets  $\{s_1, \dots, s_k\}$  from  $\{t_1, \dots, t_k\}$ . See [24].

**Questions.** Are there superlinear conditional lower bounds for all-pairs min-cut/Gomory-Hu tree construction? (Refer to [6] for conditional lower bounds for variants of the problem on directed graphs.) Are there non-trivial conditional lower bounds for all-triplets approximate min-cut, or all- $k$ -sets min-cut?

[Contributed by *Robert Krauthgamer*.]

## Open Problem 20: Parameterizing string algorithms by compressibility

**Background.** The broad idea can be illustrated with a lower bound for string edit distance: Given two strings of length  $N$  whose compressed length (say, using Lempel-Ziv compression) is  $n$ , it is known that their edit distance can be computed in  $O(nN)$  time. Is it possible to prove an  $\Omega(nN)$  conditional lower bound? The known conditional lower bound [11, 1, 17] reduces CNF-SAT (with  $n$  variables) to string edit distance by creating two strings each consisting of  $O(2^{n/2})$  blocks. To make such a reduction suitable for proving  $\Omega(nN)$  lower bound, one needs to generate instead two strings whose length is much more than  $2^{n/2}$  but that compress to much less than  $2^{n/2}$ .

[Contributed by *Oren Weimann*.]

## Open Problem 21: Reductions from low complexity to high complexity

**Background.** We know that improving the runtime of our 10-Clique algorithms improves the runtime of our 100-Clique algorithms. E.g., if 10-Clique can be solved in  $O(n^5)$ , then 100-Clique can be solved in  $O(n^{50})$ . In general, we have many examples of reductions showing that a faster algorithm for a problem with best known runtime  $O(n^a)$ , implies a faster algorithm for a problem with runtime  $O(n^b)$ , where  $a \leq b$ .

*However*, we have no interesting reductions in the other way, showing that improvements over  $n^b$  imply improvements over  $n^a$ , where  $a < b$ . In particular, we do not know how to use an algorithm that solved 100-Clique in  $O(n^{50})$  or even  $O(n^{11})$  time, to speed up the known algorithms for 10-Clique.

Could it be that such reductions, from low complexity to high complexity, do not exist? It is not hard to construct artificial problems where this can be done, but what about the natural problems we typically study: Clique, Orthogonal Vectors,  $k$ -SUM, APSP, LCS, etc. Can we show that a fine-grained reduction from 10-Clique to 100-Clique is unlikely due to some surprising consequences? Another candidate is 3SUM (for which the complexity is  $n^2$ ) vs. APSP (for which the complexity is  $N^{1.5}$ , where  $N$  is the input size). We repeatedly ask if faster 3SUM implies faster APSP, but maybe proving such a result (via fine-grained reductions) has unexpected consequences?

On the other hand, it would be of great interest to find examples of such reductions between interesting and natural problems.

[Contributed by *Amir Abboud*.]

## Open Problem 22: Stable matching in the two-list model

**Background.** Gale and Shapley's stable matching [40] algorithm runs in  $O(n^2)$  time (linear in the input size) and it is known that  $\Omega(n^2)$  is optimal if the preference lists are arbitrary. Künnemann, Moeller, Paturi, and Schneider [56] studied the complexity of stable matching when the preference lists are constrained, and encoded in some succinct manner. Many succinct input models nonetheless require  $n^{2-o(1)}$  time, conditioned on SETH.

**Question.** A problem left open by [56] is *two-list stable matching*. A matching market in the two-list model consists of two sets  $M$  and  $W$ , both of size  $n$ , and permutations  $\pi_1, \pi_2$  on  $M$  and  $\sigma_1, \sigma_2$  on  $W$ . The preference list of each agent  $m \in M$  is either  $\sigma_1$  or  $\sigma_2$  and the preference list of each agent  $w \in W$  is either  $\pi_1$  or  $\pi_2$ . The input size is  $O(n)$ . The goal is to find a stable matching in the resulting matching market. Can this problem be solved in linear time, or is there a superlinear conditional lower bound?

**Main paper reference:** Kuennemann et al. [56].

[Contributed by *Stefan Schneider*.]

### Open Problem 23: Boolean vs. real maximum inner product

**Background.** In the *maximum inner product* problem we are given two sets of  $d$ -dimensional vectors  $U$  and  $V$  of size  $n$  as well as a threshold  $l$ . The problem is to decide if there is a pair  $u \in U, v \in V$  such that their inner product  $u \cdot v$  is at least  $l$ . If the vectors are Boolean, then a randomized algorithm by Alman and Williams [9] solves the problem in time  $n^{2-1/\Theta(c \log^2 c)}$  where  $d = c \log n$ . In contrast, if the vectors are real or integer, then using ray-shooting techniques [58] we can solve the problem in time  $n^{2-1/\Theta(d)}$ . This leaves a large gap between the two problems. In particular, the Boolean case is strongly subquadratic if  $d = O(\log n)$ , while the real case is only strongly subquadratic for constant  $d$ . The conditional lower bounds of [9] show that any  $n^{2-\epsilon}$  algorithm when  $d = \omega(\log n)$  refutes SETH.

**Questions.** Can the gap between the boolean and integer/real case be closed, with a better maximum inner product algorithm? If the gap is natural, can it be explained with a stronger conditional lower bound on (real or integer) maximum inner product?

[Contributed by *Stefan Schneider*.]

### Open Problem 24: Hardness of Approximating NP-hard Problems

**Background.** Many approximation algorithms for NP-hard problems run in polynomial time, but not linear time. This is often due to the use of general LP or SDP solvers, but not always. To take two examples, the *chromatic index* (edge coloring) and *minimum degree spanning tree* problems are NP-hard, but can both be approximated to within 1 of optimal in  $\tilde{O}(m\sqrt{n})$  time [36] and  $\tilde{O}(mn)$  time [35], respectively.

**Question.** Prove superlinear conditional lower bounds on the time complexity of *any* approximation problem, whose exact version is NP-hard.

[Contributed by *Seth Pettie*.]

## Open Problem 25: Chromatic index/edge coloring

**Background.** The *chromatic index* of a graph is the least number of colors needed for a proper edge-coloring. Vizing’s theorem implies that the chromatic index is either  $\Delta$  or  $\Delta + 1$  (where  $\Delta$  is the maximum degree), but determining which one is NP-hard. The NP-hardness reduction of Holyer [48] reduces 3SAT to a 3-regular graph on  $O(n)$  vertices, so the ETH implies a  $2^{\Omega(n)}$  lower bound. There is an  $O^*(2^m)$  algorithm for chromatic index, by reduction to vertex coloring, so the hardness is well understood when  $m = O(n)$ .

**Questions.** Does the ETH rule out a  $2^{o(m)}$  algorithm for chromatic index on dense graphs? Is there, for example, an  $n^{O(n)}$  or  $2^{n^{2-\epsilon}}$ -time algorithm?

[Contributed by *Marek Cygan*.]

## Open Problem 26: Communication Complexity of Approximate Hamming Distance

**Background.** Consider strings  $P$  of length  $n$  and  $T$  of length  $2n$ . Alice has the whole of  $P$  and the first half of  $T$ . That is she has  $P$  and  $T[0, \dots, n - 1]$ . Bob has the second half of  $T$ , that is  $T[n, \dots, 2n - 1]$ . Alice sends one message to Bob and Bob has to output a  $(1 + \epsilon)$  multiplicative approximation of  $\text{HD}(P, T[i, \dots, i + n])$  for all  $i \in [n]$  where HD is the Hamming Distance.

In [25] a  $O(\sqrt{n} \log n / \epsilon^2)$  bit communication protocol was given.

**Question.** Is there a matching lower bound for the randomized one-way communication complexity of this problem?

**Main paper reference.** Clifford and Starikovskaya [25].

[Contributed by *Raphaël Clifford*.]

## References

- [1] A. Abboud, A. Backurs, and V. Vassilevska Williams. Tight hardness results for LCS and other sequence similarity measures. In *Proceedings 56th Annual IEEE Symposium on Foundations of Computer Science (FOCS)*, pages 59–78, 2015.
- [2] A. Abboud and V. Vassilevska Williams. Popular conjectures imply strong lower bounds for dynamic problems. In *Proceedings 55th IEEE Symposium on Foundations of Computer Science (FOCS)*, pages 434–443, 2014.
- [3] Amir Abboud and Søren Dahlgaard. Popular conjectures as a barrier for dynamic planar graph algorithms. In *Proceedings 57th Annual IEEE Symposium on Foundations of Computer Science (FOCS)*, pages 477–486, 2016.

- [4] Amir Abboud, Fabrizio Grandoni, and Virginia Vassilevska Williams. Subcubic equivalences between graph centrality problems, APSP and diameter. In *Proceedings of the 26th Annual ACM-SIAM Symposium on Discrete Algorithms (SODA)*, pages 1681–1697, 2015.
- [5] Amir Abboud, Virginia Vassilevska Williams, and Joshua R. Wang. Approximation and fixed parameter subquadratic algorithms for radius and diameter in sparse graphs. In *Proceedings of the 27th Annual ACM-SIAM Symposium on Discrete Algorithms (SODA)*, pages 377–391, 2016.
- [6] Amir Abboud, Virginia Vassilevska Williams, and Huacheng Yu. Matching triangles and basing hardness on an extremely popular conjecture. In *Proceedings 47th Annual ACM Symposium on Theory of Computing (STOC)*, pages 41–50, 2015.
- [7] Ittai Abraham, Shiri Chechik, and Sebastian Krinninger. Fully dynamic all-pairs shortest paths with worst-case update-time revisited. In *Proceedings of the 28th Annual ACM-SIAM Symposium on Discrete Algorithms (SODA)*, pages 440–452, 2017.
- [8] Udit Agarwal and Vijaya Ramachandran. Fine-grained complexity and conditional hardness for sparse graphs. *CoRR*, abs/1611.07008, 2016.
- [9] Josh Alman and Ryan Williams. Probabilistic polynomials and hamming nearest neighbors. In *Proceedings 56th Annual IEEE Symposium on Foundations of Computer Science (FOCS)*. IEEE, 2015.
- [10] Amihod Amir, Timothy M. Chan, Moshe Lewenstein, and Noa Lewenstein. On hardness of jumbled indexing. In *International Colloquium on Automata, Languages and Programming (ICALP)*, pages 114–125, 2014.
- [11] A. Backurs and P. Indyk. Edit distance cannot be computed in strongly subquadratic time (unless SETH is false). In *Proceedings 47th Annual ACM Symposium on Theory of Computing (STOC)*, pages 51–58, 2015.
- [12] I. Baran, E. D. Demaine, and M. Pătraşcu. Subquadratic algorithms for 3SUM. *Algorithmica*, 50(4):584–596, 2008.
- [13] L. Barba, J. Cardinal, J. Iacono, S. Langerman, A. Ooms, and N. Solomon. Subquadratic algorithms for algebraic generalizations of 3SUM. *CoRR*, abs/1612.02384, 2016.
- [14] Anand Bhargat, Ramesh Hariharan, Telikepalli Kavitha, and Debmalya Panigrahi. An  $o(mn)$  Gomory-Hu tree construction algorithm for unweighted graphs. In *Proceedings of the 39th Annual ACM Symposium on Theory of Computing (STOC)*, pages 605–614, 2007.
- [15] Henrik Björklund and Sergei G. Vorobyov. A combinatorial strongly subexponential strategy improvement algorithm for mean payoff games. *Discrete Applied Mathematics*, 155(2):210–229, 2007.
- [16] Lubos Brim, Jakub Chaloupka, Laurent Doyen, Raffaella Gentilini, and Jean-François Raskin. Faster algorithms for mean-payoff games. *Formal Methods in System Design*, 38(2):97–118, 2011.

- [17] K. Bringmann and M. Künnemann. Quadratic conditional lower bounds for string problems and dynamic time warping. In *Proceedings 56th Annual IEEE Symposium on Foundations of Computer Science (FOCS)*, pages 79–97, 2015.
- [18] Sergio Cabello. Subquadratic algorithms for the diameter and the sum of pairwise distances in planar graphs. In *Proceedings of the 28th Annual ACM-SIAM Symposium on Discrete Algorithms (SODA)*, pages 2143–2152, 2017.
- [19] Massimo Cairo, Roberto Grossi, and Romeo Rizzi. New bounds for approximating extremal distances in undirected graphs. In *Proceedings 27th Annual ACM-SIAM Symposium on Discrete Algorithms (SODA)*, pages 363–376, 2016.
- [20] C. S. Calude, S. Jain, B. Khoussainov, W. Li, and F. Stephan. Deciding parity games in quasipolynomial time. In *Proceedings 49th Annual ACM Symposium on Theory of Computing (STOC)*, 2017.
- [21] Timothy Chan and Moshe Lewenstein. Clustered integer 3SUM via additive combinatorics. In *Proceedings 47th ACM Symposium on Theory of Computing (STOC)*, pages 31–40, 2015.
- [22] S. Chechik, D. Larkin, L. Roditty, G. Schoenebeck, R. E. Tarjan, and V. Vassilevska Williams. Better approximation algorithms for the graph diameter. In *Proceedings of the 25th Annual ACM-SIAM Symposium on Discrete Algorithms (SODA)*, pages 1041–1052, 2014.
- [23] Shiri Chechik, Thomas Dueholm Hansen, Giuseppe F. Italiano, Jakub Lacki, and Nikos Parotsidis. Decremental single-source reachability and strongly connected components in  $\tilde{O}(m\sqrt{n})$  total update time. In *Proceedings 57th Annual IEEE Symposium on Foundations of Computer Science (FOCS)*, pages 315–324, 2016.
- [24] Rajesh Chitnis, Lior Kamma, and Robert Krauthgamer. Tight bounds for Gomory-Hu-like cut counting. In *Proceedings 42nd International Workshop on Graph-Theoretic Concepts in Computer Science (WG)*, pages 133–144, 2016.
- [25] Raphaël Clifford and Tatiana A. Starikovskaya. Approximate hamming distance in a stream. In *Proceedings 43rd International Colloquium on Automata, Languages, and Programming (ICALP)*, pages 20:1–20:14, 2016.
- [26] Marek Cygan, Fedor V. Fomin, Lukasz Kowalik, Daniel Lokshtanov, Dániel Marx, Marcin Pilipczuk, Michal Pilipczuk, and Saket Saurabh. *Parameterized Algorithms*. Springer, 2015.
- [27] Søren Dahlgaard. On the hardness of partially dynamic graph problems and connections to diameter. In *Proceedings 43rd International Colloquium on Automata, Languages, and Programming (ICALP)*, pages 48:1–48:14, 2016.
- [28] C. Demetrescu and G. F. Italiano. A new approach to dynamic all pairs shortest paths. *Journal of the ACM*, 51(6):968–992, 2004.
- [29] Krzysztof Diks and Piotr Sankowski. Dynamic plane transitive closure. In *Proceedings of 15th Annual European Symposium on Algorithms (ESA)*, pages 594–604, 2007.
- [30] D. Dor, S. Halperin, and U. Zwick. All-pairs almost shortest paths. *SIAM Journal on Computing*, 29(5):1740–1759, 2000.

- [31] Fedor V. Fomin, Daniel Lokshantov, Michal Pilipczuk, Saket Saurabh, and Marcin Wrochna. Fully polynomial-time parameterized computations for graphs and matrices of low treewidth. In *Proceedings 28th Annual ACM-SIAM Symposium on Discrete Algorithms (SODA)*, pages 1419–1432, 2017.
- [32] Fedor V. Fomin, Fahad Panolan, M. S. Ramanujan, and Saket Saurabh. On integer programming and the path-width of the constraint matrix. *CoRR*, abs/1607.05342v2, 2016.
- [33] M. L. Fredman. How good is the information theory bound in sorting? *Theoretical Computer Science*, 1(4):355–361, 1976.
- [34] A. Freund. Improved subquadratic 3SUM. *Algorithmica*, pages 1–19, 2015.
- [35] M. Fürer and B. Raghavachari. Approximating the minimum-degree Steiner tree to within one of optimal. *J. Algorithms*, 17(3):409–423, 1994.
- [36] H. Gabow, T. Nishizeki, O. Kariv, D. Leven, and O. Terada. Algorithms for edge-coloring graphs. Technical Report 41/85, Tohoku University, 1985.
- [37] Harold N. Gabow. A matroid approach to finding edge connectivity and packing arborescences. *Journal of Computer and System Sciences*, 50(2):259–273, 1995.
- [38] Harold N. Gabow. Using expander graphs to find vertex connectivity. *J. ACM*, 53(5):800–844, 2006.
- [39] Anka Gajentaan and Mark H. Overmars. On a class of  $O(n^2)$  problems in computational geometry. *Comput. Geom.*, 45(4):140–152, 2012.
- [40] David Gale and Lloyd S. Shapley. College admissions and the stability of marriage. *The American Mathematical Monthly*, 69(1):9–15, 1962.
- [41] O. Gold and M. Sharir. Improved bounds for 3SUM,  $K$ -SUM, and linear degeneracy. *CoRR*, abs/1512.05279, 2015.
- [42] Isaac Goldstein, Tsvi Kopelowitz, Moshe Lewenstein, and Ely Porat. How hard is it to find (honest) witnesses? In *Proceedings 24th Annual European Symposium on Algorithms (ESA)*, pages 45:1–45:16, 2016.
- [43] R. E. Gomory and T. C. Hu. Multi-terminal network flows. *Journal of the Society for Industrial and Applied Mathematics*, 9, 1961.
- [44] A. Grønlund and S. Pettie. Threesomes, degenerates, and love triangles. In *Proceedings 55th IEEE Symposium on Foundations of Computer Science (FOCS)*, pages 621–630, 2014.
- [45] Joel Hass, J. C. Lagarias, and Nicholas Pippenger. The computational complexity of knot and link problems. *J. ACM*, 46(2):185–211, 1999.
- [46] M. Henzinger, S. Krinninger, D. Nanongkai, and T. Saranurak. Unifying and strengthening hardness for dynamic problems via the online matrix-vector multiplication conjecture. In *Proceedings 47th Annual ACM Symposium on Theory of Computing (STOC)*, pages 21–30, 2015.

- [47] Monika Henzinger, Satish Rao, and Di Wang. Local flow partitioning for faster edge connectivity. In *Proceedings 28th ACM-SIAM Symposium on Discrete Algorithms (SODA)*, pages 1919–1938, 2017.
- [48] Ian Holyer. The NP-completeness of edge-coloring. *SIAM J. Comput.*, 10(4):718–720, 1981.
- [49] A. Itai and M. Rodeh. Finding a minimum circuit in a graph. *SIAM J. Comput.*, 7(4):413–423, 1978.
- [50] W. Jaco and J. L. Tolleson. Algorithms for the complete decomposition of a closed 3-manifold. *Ill. J. Math.*, 39:358–406, 1995.
- [51] M. Jurdziński and R. Lazić. Succinct progress measures for solving parity games. *CoRR*, abs/1702.05051, 2017.
- [52] Marcin Jurdziński. Deciding the winner in parity games is in  $UP \cap co-UP$ . *Information Processing Letters*, 68(3):119–124, 1998.
- [53] Marcin Jurdziński, Mike Paterson, and Uri Zwick. A Deterministic Subexponential Algorithm for Solving Parity Games. *SIAM Journal on Computing*, 38(4):1519–1532, 2008.
- [54] Ken-ichi Kawarabayashi and Mikkel Thorup. Deterministic global minimum cut of a simple graph in near-linear time. In *Proceedings 47th ACM Symposium on Theory of Computing (STOC)*, pages 665–674, 2015.
- [55] T. Kopelowitz, S. Pettie, and E. Porat. Higher lower bounds from the 3SUM conjecture. In *Proceedings 27th Annual ACM-SIAM Symposium on Discrete Algorithms (SODA)*, pages 1272–1287, 2016.
- [56] Marvin Künnemann, Daniel Moeller, Ramamohan Paturi, and Stefan Schneider. Subquadratic algorithms for succinct stable matching. *CoRR*, abs/1510.06452, 2015.
- [57] Yin Tat Lee and Aaron Sidford. Efficient inverse maintenance and faster algorithms for linear programming. In *Proceedings 56th Annual IEEE Symposium on Foundations of Computer Science (FOCS)*, pages 230–249, 2015.
- [58] Jiří Matoušek. Efficient partition trees. *Discrete & Computational Geometry*, 8(1):315–334, 1992.
- [59] Jakub Pachocki, Liam Roditty, Aaron Sidford, Roei Tov, and Virginia Vassilevska Williams. Approximating cycles in directed graphs: Fast algorithms for girth and roundtrip spanners. *CoRR*, abs/1611.00721, 2016.
- [60] Debmalya Panigrahi. Gomory-Hu trees. In Ming-Yang Kao, editor, *Encyclopedia of Algorithms*, pages 858–861. Springer New York, 2016.
- [61] Christos H. Papadimitriou. On the complexity of integer programming. *J. ACM*, 28(4):765–768, 1981.
- [62] L. Roditty and V. Vassilevska Williams. Fast approximation algorithms for the diameter and radius of sparse graphs. In *Proceedings 45th ACM Symposium on Theory of Computing (STOC)*, pages 515–524, 2013.



- [63] Liam Roditty and Virginia Vassilevska Williams. Subquadratic time approximation algorithms for the girth. In *Proceedings of the 23rd Annual ACM-SIAM Symposium on Discrete Algorithms (SODA)*, pages 833–845, 2012.
- [64] Barna Saha. Language edit distance and maximum likelihood parsing of stochastic grammars: Faster algorithms and connection to fundamental graph problems. In *Proceedings 56th Annual IEEE Symposium on Foundations of Computer Science (FOCS)*, pages 118–135, 2015.
- [65] M. Thorup. Worst-case update times for fully-dynamic all-pairs shortest paths. In *Proceedings 37th ACM Symposium on Theory of Computing (STOC)*, pages 112–119, 2005.
- [66] V. Vassilevska Williams and R. Williams. Subcubic equivalences between path, matrix and triangle problems. In *Proceedings 51st Annual IEEE Symposium on Foundations of Computer Science (FOCS)*, pages 645–654, 2010.
- [67] R. Yuster and U. Zwick. Finding even cycles even faster. *SIAM J. Discrete Mathematics*, 10(2):209–222, 1997.